



**BUREAU
VERITAS**

Emergency Response Service (ERS)

January 2010

**Rule Note
NR 556 DT R00 E**

**Marine Division
92571 Neuilly sur Seine Cedex – France
Tel: + 33 (0)1 55 24 70 00 – Fax: + 33 (0)1 55 24 70 25
Marine website: <http://www.veristar.com>
Email: veristarinfo@bureauveritas.com
© 2009 Bureau Veritas - All rights reserved**



**BUREAU
VERITAS**

ARTICLE 1

1.1. - BUREAU VERITAS is a Society the purpose of whose Marine Division (the "Society") is the classification ("Classification") of any ship or vessel or structure of any type or part of it or system therein collectively hereinafter referred to as a "Unit" whether linked to shore, river bed or sea bed or not, whether operated or located at sea or in inland waters or partly on land, including submarines, hovercrafts, drilling rigs, offshore installations of any type and of any purpose, their related and ancillary equipment, subsea or not, such as well head and pipelines, mooring legs and mooring points or otherwise as decided by the Society.

The Society:

- prepares and publishes Rules for classification, Guidance Notes and other documents ("Rules");
- issues Certificates, Attestations and Reports following its interventions ("Certificates");
- publishes Registers.

1.2. - The Society also participates in the application of National and International Regulations or Standards, in particular by delegation from different Governments. Those activities are hereafter collectively referred to as "Certification".

1.3. - The Society can also provide services related to Classification and Certification such as ship and company safety management certification; ship and port security certification, training activities; all activities and duties incidental thereto such as documentation on any supporting means, software, instrumentation, measurements, tests and trials on board.

1.4. - The interventions mentioned in 1.1., 1.2. and 1.3. are referred to as "Services". The party and/or its representative requesting the services is hereinafter referred to as the "Client". **The Services are prepared and carried out on the assumption that the Clients are aware of the International Maritime and/or Offshore Industry (the "Industry") practices.**

1.5. - The Society is neither and may not be considered as an Underwriter, Broker in ship's sale or chartering, Expert in Unit's valuation, Consulting Engineer, Controller, Naval Architect, Manufacturer, Shipbuilder, Repair yard, Charterer or Shipowner who are not relieved of any of their expressed or implied obligations by the interventions of the Society.

ARTICLE 2

2.1. - Classification is the appraisal given by the Society for its Client, at a certain date, following surveys by its Surveyors along the lines specified in Articles 3 and 4 hereafter on the level of compliance of a Unit to its Rules or part of them. This appraisal is represented by a class entered on the Certificates and periodically transcribed in the Society's Register.

2.2. - Certification is carried out by the Society along the same lines as set out in Articles 3 and 4 hereafter and with reference to the applicable National and International Regulations or Standards.

2.3. - **It is incumbent upon the Client to maintain the condition of the Unit after surveys, to present the Unit for surveys and to inform the Society without delay of circumstances which may affect the given appraisal or cause to modify its scope.**

2.4. - The Client is to give to the Society all access and information necessary for the safe and efficient performance of the requested Services. The Client is the sole responsible for the conditions of presentation of the Unit for tests, trials and surveys and the conditions under which tests and trials are carried out.

ARTICLE 3

3.1. - **The Rules, procedures and instructions of the Society take into account at the date of their preparation the state of currently available and proven technical knowledge of the Industry. They are not a standard or a code of construction neither a guide for maintenance, a safety handbook or a guide of professional practices, all of which are assumed to be known in detail and carefully followed at all times by the Client.**

Committees consisting of personalities from the Industry contribute to the development of those documents.

3.2. - **The Society only is qualified to apply its Rules and to interpret them. Any reference to them has no effect unless it involves the Society's intervention.**

3.3. - The Services of the Society are carried out by professional Surveyors according to the applicable Rules and to the Code of Ethics of the Society. Surveyors have authority to decide locally on matters related to classification and certification of the Units, unless the Rules provide otherwise.

3.4. - **The operations of the Society in providing its Services are exclusively conducted by way of random inspections and do not in any circumstances involve monitoring or exhaustive verification.**

ARTICLE 4

4.1. - The Society, acting by reference to its Rules:

- reviews the construction arrangements of the Units as shown on the documents presented by the Client;
- conducts surveys at the place of their construction;
- classes Units and enters their class in its Register;
- surveys periodically the Units in service to note that the requirements for the maintenance of class are met.

The Client is to inform the Society without delay of circumstances which may cause the date or the extent of the surveys to be changed.

ARTICLE 5

5.1. - **The Society acts as a provider of services. This cannot be construed as an obligation bearing on the Society to obtain a result or as a warranty.**

5.2. - **The certificates issued by the Society pursuant to 5.1. here above are a statement on the level of compliance of the Unit to its Rules or to the documents of reference for the Services provided for.**

In particular, the Society does not engage in any work relating to the design, building, production or repair checks, neither in the operation of the Units or in their trade, neither in any advisory services, and cannot be held liable on those accounts. Its certificates cannot be construed as an implied or express warranty of safety, fitness for the purpose, seaworthiness of the Unit or of its value for sale, insurance or chartering.

5.3. - **The Society does not declare the acceptance or commissioning of a Unit, nor of its construction in conformity with its design, that being the exclusive responsibility of its owner or builder, respectively.**

MARINE DIVISION GENERAL CONDITIONS

5.4. - The Services of the Society cannot create any obligation bearing on the Society or constitute any warranty of proper operation, beyond any representation set forth in the Rules, of any Unit, equipment or machinery, computer software of any sort or other comparable concepts that has been subject to any survey by the Society.

ARTICLE 6

6.1. - The Society accepts no responsibility for the use of information related to its Services which was not provided for the purpose by the Society or with its assistance.

6.2. - **If the Services of the Society cause to the Client a damage which is proved to be the direct and reasonably foreseeable consequence of an error or omission of the Society, its liability towards the Client is limited to ten times the amount of fee paid for the Service having caused the damage, provided however that this limit shall be subject to a minimum of eight thousand (8,000) Euro, and to a maximum which is the greater of eight hundred thousand (800,000) Euro and one and a half times the above mentioned fee.**

The Society bears no liability for indirect or consequential loss such as e.g. loss of revenue, loss of profit, loss of production, loss relative to other contracts and indemnities for termination of other agreements.

6.3. - All claims are to be presented to the Society in writing within three months of the date when the Services were supplied or (if later) the date when the events which are relied on were first known to the Client, and any claim which is not so presented shall be deemed waived and absolutely barred. Time is to be interrupted thereafter with the same periodicity.

ARTICLE 7

7.1. - Requests for Services are to be in writing.

7.2. - **Either the Client or the Society can terminate as of right the requested Services after giving the other party thirty days' written notice, for convenience, and without prejudice to the provisions in Article 8 hereunder.**

7.3. - The class granted to the concerned Units and the previously issued certificates remain valid until the date of effect of the notice issued according to 7.2. here above subject to compliance with 2.3. here above and Article 8 hereunder.

7.4. - The contract for classification and/or certification of a Unit cannot be transferred neither assigned.

ARTICLE 8

8.1. - The Services of the Society, whether completed or not, involve, for the part carried out, the payment of fee upon receipt of the invoice and the reimbursement of the expenses incurred.

8.2. - **Overdue amounts are increased as of right by interest in accordance with the applicable legislation.**

8.3. - **The class of a Unit may be suspended in the event of non-payment of fee after a first unfruitful notification to pay.**

ARTICLE 9

9.1. - The documents and data provided to or prepared by the Society for its Services, and the information available to the Society, are treated as confidential. However:

- clients have access to the data they have provided to the Society and, during the period of classification of the Unit for them, to the classification file consisting of survey reports and certificates which have been prepared at any time by the Society for the classification of the Unit;
- copy of the documents made available for the classification of the Unit and of available survey reports can be handed over to another Classification Society, where appropriate, in case of the Unit's transfer of class;
- the data relative to the evolution of the Register, to the class suspension and to the survey status of the Units, as well as general technical information related to hull and equipment damages, are passed on to IACS (International Association of Classification Societies) according to the association working rules;
- the certificates, documents and information relative to the Units classed with the Society may be reviewed during certifying bodies audits and are disclosed upon order of the concerned governmental or inter-governmental authorities or of a Court having jurisdiction.

The documents and data are subject to a file management plan.

ARTICLE 10

10.1. - Any delay or shortcoming in the performance of its Services by the Society arising from an event not reasonably foreseeable by or beyond the control of the Society shall be deemed not to be a breach of contract.

ARTICLE 11

11.1. - In case of diverging opinions during surveys between the Client and the Society's surveyor, the Society may designate another of its surveyors at the request of the Client.

11.2. - Disagreements of a technical nature between the Client and the Society can be submitted by the Society to the advice of its Marine Advisory Committee.

ARTICLE 12

12.1. - Disputes over the Services carried out by delegation of Governments are assessed within the framework of the applicable agreements with the States, international Conventions and national rules.

12.2. - Disputes arising out of the payment of the Society's invoices by the Client are submitted to the Court of Nanterre, France.


12.3. - **Other disputes over the present General Conditions or over the Services of the Society are exclusively submitted to arbitration, by three arbitrators, in London according to the Arbitration Act 1996 or any statutory modification or re-enactment thereof. The contract between the Society and the Client shall be governed by English law.**

ARTICLE 13

13.1. - **These General Conditions constitute the sole contractual obligations binding together the Society and the Client, to the exclusion of all other representation, statements, terms, conditions whether express or implied. They may be varied in writing by mutual agreement.**

13.2. - The invalidity of one or more stipulations of the present General Conditions does not affect the validity of the remaining provisions.

13.3. - The definitions herein take precedence over any definitions serving the same purpose which may appear in other documents issued by the Society.



RULE NOTE NR 556

NR 556 Emergency Response Service

SECTION 1	EMERGENCY RESPONSE SERVICE (ERS)
APPENDIX 1	ERS-M (EMERGENCY RESPONSE SERVICE - MOORING) SCOPE OF WORK

Section 1 Emergency Response Service (ERS)

1	General	5
	1.1 Aim of Service	
	1.2 Additional Class notations	
	1.3 International Regulations	
2	Application	5
	2.1 Type of vessels concerned	
	2.2 Type of Services	
3	Establishment and maintenance of the Services	5
	3.1 Establishment of the Services	
	3.2 Establishment of ERS-S	
	3.3 Establishment of ERS-H	
	3.4 Establishment of ERS-M	
	3.5 Maintenance	
4	Emergency case	7
	4.1 General	
	4.2 ERS-S	
	4.3 ERS-H	
	4.4 ERS-M	
5	Test emergency case	7
	5.1	

Appendix 1 ERS-M (Emergency Response Service - Mooring) Scope of Work

1	General	8
	1.1 Application	
2	Definitions	8
	2.1 Mooring line tension	
	2.2 Usage factor	
	2.3 Mooring force	
	2.4 Design mooring force	
	2.5 Horizontal excursions	
3	Assumptions, units and required documents	9
	3.1	
	3.2 Assumptions on the unit	
	3.3 Assumptions on the environmental data	
	3.4 Units	
	3.5 Required documents	
4	Establishment of the Services	10
	4.1 General	
	4.2 Configurations considered	
	4.3 Methodology	
	4.4 Side documentation	

- 5.1 General
- 5.2 F(P)SO – spread mooring
- 5.3 F(P)SO – turret mooring
- 5.4 Buoys

SECTION 1

EMERGENCY RESPONSE SERVICE (ERS)

Symbols

BV	: Bureau Veritas
ERS	: Emergency Response Service
Unit	: Ship, barge or buoy
Vessel	: Ship or barge
RAO	: Response Amplitude Operator
VWBM	: Vertical Wave Bending Moment
VWSF	: Vertical Wave Shear Force
SWSF	: Still Water Shear Force
Hs	: Significant wave height
L	: Vessel length between perpendiculars
V _{max}	: Ship maximum speed

1 General

1.1 Aim of Service

1.1.1 The aim of the ERS is to provide technical assistance to units in case of a maritime accident at sea, by providing information on their remaining strength and stability in the resulting damaged condition.

This Service, requested as mentioned in [1.3], can be provided by various organizations involved in the maritime sector, including Classification Societies.

The present Rule Note describes the three different types of Services that can be provided by BV: **ERS-S** (Strength), **ERS-H** (Hydrodynamic) and **ERS-M** (Mooring).

1.2 Additional Class notations

1.2.1 The associated additional Class notations: **ERS-S**, **ERS-H** and **ERS-M** can be granted in the particular case of BV classed units for which the ERS Service(s) is(are) also contracted with BV.

1.3 International Regulations

1.3.1 **ERS-S** is intended to comply with the provisions stipulated in MARPOL Annex I, Chapter 5, Reg.37 "Shipboard oil pollution emergency plan", regarding the prevention of pollution arising from an oil pollution incident.

Access to computerized stability and longitudinal strength databases are mandatory for oil tankers above 5000 tons deadweight.

ERS-S is also in compliance with the requirements of ISM Code Article 1.3 and Regulation 8.3.

2 Application

2.1 Type of units concerned

2.1.1 ERS can be contracted for any existing unit, either classed by BV or by another Class; however the additional Class notations can only be granted to BV classed units.

ERS can not be contracted for vessels below 65 m in length.

ERS-M is solely intended for permanently moored units, such as F(P)SO and buoys; **ERS-S** and **ERS-H** are intended for ships and barges only.

2.2 Type of Services

2.2.1 As mentioned above, ERS can be contracted for three different types of Services.

2.2.2 ERS-S

ERS-S corresponds to damage longitudinal strength and damage stability analyses. It aims at providing information on the remaining hull strength and stability after the accident.

2.2.3 ERS-H

ERS-H aims at providing limits of navigation, based on VWBM and VWSF direct calculations for the accidental site sea-states, instead of empirical Rules formulae.

ERS-H is only applied in complement to ERS-S. It aims at providing maximum environmental conditions (Hs), heading restriction, or speed limit. These limits of navigation are given for hull girder strength only.

2.2.4 ERS-M

ERS-M corresponds to damaged mooring analyses for permanently moored units. It aims at providing information on the remaining capacities of the mooring system after the failure of one or several mooring lines and the potential failure of an additional mooring line.

3 Establishment and maintenance of the Services

3.1 Establishment of the Services

3.1.1 ERS comprises the establishment of the unitspecific technical data. They include computer models of the unit based on information provided by the Client in order to be quickly able to perform calculations of damage stability, damage strength, damage mooring, and/or hydrodynamic behavior of the unit, depending on the Service(s) contracted.

The Client is to supply BV with the documentation listed in [3.2], [3.3] and/or [3.4] depending on the Service(s) contracted.

BV will provide a blank customized "emergency form" (including protocol for the call) to be filled and sent in case of emergency or test by the Client.

The Client will be noticed when the Service(s) become(s) operational and will receive the above "emergency form" together with side documentations.

3.2 Establishment of ERS-S

3.2.1 Models

For ERS-S, two different computer models are established by BV:

- An hydrostatic model of the vessel in order to assess the equilibrium (displacement, draught, trim, list), the intact stability, the damage stability and the still water hull girder loads
- A 2D structural model of the vessel main sections in order to assess the intact and damage strength of longitudinal members of the hull structure.

3.2.2 Documents to be provided

In order to build these two models, the following documents are to be provided by the Client:

- General arrangement drawing
- Capacity plan
- Print out from the loading computer, if any, showing the naming and numbering convention of the capacities
- Hull lines drawing (or off-set tables)
- Longitudinal distribution of lightship weight
- Loading manual and/or trim and stability manual (with longitudinal strength calculation)
- Free-Board Report
- Coordinates (X, Y, Z) of all openings (doors, air pipes, ventilators, hatches...) located on exposed deck with indication of their means of closing (usually shown on Free-Board Plan)
- Permissible still-water bending moments and shear forces
- Midship section drawings
- Profile and decks drawings
- Shell expansion drawings
- Cargo holds structure drawings
- Engine room structure drawings
- Fore part structure drawings
- Aft part structure drawings.

3.2.3 Side documentation

The side documentation provided by BV to the Client when the Service becomes effective is:

- A capacity table and sketch with the naming convention and the numbering based on the loading computer convention
- Stability booklet detailing lever arm curve with the stability criteria and vessel equilibrium (draught, trim and list) in intact condition at least for two loading cases (full load and ballast)
- Longitudinal strength booklet detailing the calculated values of still water bending moments and shear forces and comparison with intact allowable values.

3.3 Establishment of ERS-H

3.3.1 Model

Three hydrodynamic models (minimum and maximum draughts for the VWBM and intermediate alternate draught for VWSF) specified in the loading manual and/or Trim and Stability booklet are established.

The RAOs of VWBM and VWSF are calculated as follow:

- For frequencies between 0.1 and 2 rad/s, with a step of 0.05 rad/s
- Every 45° headings
- On 9 sections along the vessel length started at 0.1L up to 0.9L, and regularly distributed
- Three speeds : 0, 1/3 of V_{max} and 2/3 of V_{max} .

Note 1: The intermediate alternate draught is normally selected based on the loading case giving maximum SWSF in the loading manual or in the Trim and Stability booklet.

3.3.2 Documents to be provided

- Hull lines drawings (or off-set tables)
- Loading manual including the three modeled loading conditions.

3.3.3 Side documentation

BV will provide the Client with the RAOs of VWBM and VWSF.

3.4 Establishment of ERS-M

3.4.1 Model and scenarios

A computer model and scenarios are established by BV as detailed in App 1.

The documents to be provided by the Client are detailed in App 1.

3.4.2 Side documentation

The side documentation provided by BV is detailed in App 1. It at least includes:

- Mooring line naming convention
- Detailed environmental loads (not relevant for buoys)
- Polar plots of offsets and tensions (not relevant for buoys)
- Mooring force, excursion and tug pull (for buoys only).

3.5 Maintenance

3.5.1 When the Service(s) is(are) effective, and in case of modifications or alterations brought to the unit including any data affecting the models prepared by BV, the Client is to inform BV so that the concerned technical data and models are to be updated.

BV will then inform the Client when the updated Service(s) become operational. Updated blank customized “emergency form” and updated side documentation will be sent to the Client.

4 Emergency case

4.1 General

4.1.1 In case of emergency, the Client will initiate the mobilization of the BV ERS team by calling the BV ERS phone number mentioned in the “emergency form”.

The Client will advise BV ERS team about the unit condition by sending the “emergency form” received from BV, duly completed. By fully completing the “emergency form”, the Client will describe the unit condition before damage, the extent of damage and the corrective actions proposed to be taken.

Normally within two hours after the initial phone call from Client, BV ERS team will acknowledge receipt of the “emergency form” and will confirm their readiness to start the analyses aiming at providing the required information pertinent to the damage sustained by the unit. As soon as possible thereafter, BV ERS team will exchange with the Client in order to confirm the common understanding on the data sent by the Client, on the content of the analyses they will perform and on the results that can be expected from these analyses.

BV ERS team will perform analysis in order to provide information on the described damage, final and intermediate situations given by the Client, taking into account the fact that the crew onboard vessel do not have usually the means to analyze and/or model damaged hull structures and/or mooring to derive the residual strength after damage.

Regular contacts between BV ERS team and Client will be kept until demobilization. The Client will keep BV informed of modifications to the “emergency form” data.

On completion of BV ERS team work, Client will give written notice (by fax or email) of the demobilization of BV ERS team upon receipt of requested information.

4.2 ERS-S

4.2.1 For **ERS-S**, BV ERS team is composed of staff experienced in stability and staff experienced in hull structure.

BV ERS team will provide the Client with at least the following information for initial damage, intermediate and final loading conditions proposed by the Client:

- Vessel equilibrium (displacement, draught, trim, list)
- Vessel hydrostatic stability
- Vessel still water hull girder loads
- Allowable damage still water hull girder loads.

BV ERS team will provide opinion on the initial damage situation and the proposed scenarios in terms of hydrostatic stability and strength of the vessel based on the conditions as described by the Client.

In case of stability issue without hull structure failure, BV ERS team will compare the obtained still water hull girder loads of the loading cases under analysis with the allowable still water hull girder loads of the vessel.

In the case the still water hull girder load values exceed allowable still water hull girder loads of the vessel, BV ERS team may check if new allowable still water hull girder loads can be issued taking into account the present and forecasted environmental conditions provided by the Client. Then, BV ERS team will compare the obtained still water hull girder loads of the loading cases analyzed with the new allowable still water hull girder loads of the vessel.

In case of hull structure failure, with or without stability issue, BV ERS team will determine new allowable still water hull girder loads taking into account the hull structure damage (location, extent, loading of adjacent tanks) in conjunction with the present and forecasted environmental conditions provided by the Client. Then, BV ERS team will compare the estimated still water hull girder loads of the loading cases analyzed with the new allowable still water hull girder loads of the vessel.

4.3 ERS-H

4.3.1 For **ERS-H**, the BV ERS team is composed of same staff as for **ERS-S**.

As a complement of the remaining capacity of the hull section calculated in the scope of **ERS-S**, BV will provide limits of navigation based on hull girder strength: maximum environmental conditions (Hs), heading restriction, or speed limit.

4.4 ERS-M

4.4.1 For **ERS-M**, the BV ERS team is composed of staff experienced in mooring analyses.

BV ERS team will provide the Client with information on the remaining capacities of the mooring system to keep the unit in position after the failure of one or several mooring lines, in terms of excursions, tug pull and mooring lines tensions, as detailed in App 1.

5 Test emergency case

5.1

5.1.1 The Client is to submit to BV a test emergency case after the receipt of the written notice confirming the Service(s) contracted become operational. The aim of the test emergency case is to validate the communication procedure, technical mutual understanding and speed of response.

The procedure for the test emergency case is the same as for an actual emergency case, as described in [4] above.

APPENDIX 1

ERS-M (EMERGENCY RESPONSE SERVICE - MOORING) SCOPE OF WORK

1 General

1.1 Application

1.1.1 This document aims at describing the scope of work for Emergency Response Service for mooring (**ERS-M**).

1.1.2 **ERS-M** aims at providing information on the remaining capacities of the mooring system after the failure of a given number “n” of mooring lines and the potential failure of an additional mooring line. This will allow the Client to make an informed decision of the likely consequences, in particular on umbilical flow-line and riser system.

1.1.3 In order to speed up Bureau Veritas ERS Service, a number of pre-established mooring scenarios are analyzed before the Service enters into force.

1.1.4 This appendix describes:

- The establishment of pre-established mooring scenarios and the side documentation provided to the Client
- The Service provided in case of an emergency.

2 Definitions

2.1 Mooring line tension

2.1.1 Within this document “mooring line tension” is to be understood as follows:

- in case of calculations with a quasi dynamic approach under a specified set of metocean conditions and system conditions, mooring line tension is calculated as design tension as per NI493 Classification of Mooring Systems for Permanent Offshore Units. This value takes into account the statistical dispersion of results due to random nature of waves
- in case of static calculations without environmental loads, mooring line tension is the static tension of the mooring line for a given mooring force.

2.1.2 In both cases, tension is to be understood as an actual tension (expressed in kN) at fairlead (including both vertical and horizontal component).

2.2 Usage factor

2.2.1 Usage factor of a mooring line is defined as the following ratio:

$$\text{Usage Factor} = \frac{\text{Mooring Line Tension}}{\text{Mooring Line Breaking Load}}$$

2.2.2 Mooring line breaking load is taken as the minimum breaking load over all line segments (chains, cable, synthetic rope). Usage factor does not take into account the breaking load of other line components.

2.2.3 Usage factors are given when relevant with/without corrosion on mooring lines. In case corrosion on mooring chains is taken into account, default value is 0.4mm/year during the expected Service life of the unit (mooring line segment breaking load is reduced accordingly).

2.3 Mooring force

2.3.1 For the calculations of offloading buoys, mooring force is the horizontal static pulling force applied to the buoy representing all the actions of a shuttle tanker.

2.4 Design mooring force

2.4.1 Design mooring force is the maximum allowable value of mooring force. Its value is project specific and is assumed to be defined at design stage.

2.5 Horizontal excursions

2.5.1 Horizontal excursion under a specified set of metocean conditions and system conditions (F(P)SO) is the maximum horizontal distance during a given sea state between two positions of the reference point:

- its position calculated under these conditions
- its position at rest, without environment, in intact conditions.

2.5.2 For quasi dynamic approach, this excursion is calculated with the same methodology as a design tension as per NI493 Classification of Mooring Systems for Permanent Offshore Units. This value takes into account the statistical dispersion of results due to random nature of waves.

2.5.3 For offloading buoys, with static calculations, horizontal excursion under a specified set of system conditions is the maximum horizontal distance during a given sea state between two positions of buoy center:

- its position calculated under these conditions
- its position at rest, without any mooring force, in intact conditions.

3 Assumptions, units and required documents

3.1

3.1.1 The following assumptions are valid for both the establishment phases and the analyses performed in case of an emergency.

3.2 Assumptions on the unit

3.2.1 Following general assumptions are made during calculations:

- Clearance issues are not considered
- No offloading is considered on FSO/FPSOs
- Corrosion on mooring chains is taken into account. By default, this value is 0.4mm/year during the expected Service life of the unit
- There is no structure in close proximity to the unit under study, except otherwise specified.

3.3 Assumptions on the environmental data

3.3.1 Squalls and wind gusts

Squalls and wind gusts are not considered even if data are available in metocean specifications.

3.3.2 Return periods considered

All analyses on F(P)SOs are based on extreme metocean data from the metocean specification provided by the Client.

Different return periods of the environment and combinations of the elements are considered, as listed below:

- 100-year return period environment includes 100-year return period for the governing element and associated values (95% quantile values or 1-year return period value) for the others.
- 1-year return period environment is defined in ERS activities as a combination of 1-year return period of each element (current, wind, swell and wind-sea).
- 1-year return period for wind and current and two values combined significant wave Hs (below 1-year return period value). This value of Hs is considered omni-directional.
- 1-year return period for waves and wind with a low current (below 1-year return period value). This value of current is considered omni-directional.
- 1-year return period for waves and current with a low wind (below 1-year return period value). This value of wind is considered omni-directional.

3.4 Units

3.4.1 Maximum tension

Results in term of mooring line tension will be given under the following format:

- Tension in kN
- % of usage of line strength "usage factor" taking into account corrosion
- % of usage of line strength "usage factor" without taking into account corrosion
- Polar plots will indicate constraint provided by the Client.

3.4.2 Maximum horizontal excursion

Results in term of horizontal excursion of the unit will be given under the following format:

- Excursion in meters of the unit at the reference point
- Reference point considered:
 - either at unit center (amidships, at the centerline) for spread moored unit
 - at turret center for single point moored units
 - at buoy center for buoys
- Excursion expressed in percentage of water depth
- Polar plots will indicate constraint provided by the Client.

3.4.3 Tug pull

The intensity value will be expressed in kN. Its direction will be given from North.

It corresponds to an effective force that may be obtained by several tugs.

3.4.4 Maximum mooring force

The intensity value will be expressed in kN. This value is omni-directional.

3.5 Required documents

3.5.1 Information required for the establishment of the model is as follows:

- Hull
 - Lines plan
 - General arrangement drawing
 - Longitudinal distribution of lightship weight (vessels only)
 - Capacity plan (vessels only)
 - Loading manual and/or trim and stability manual
- Unit specific data
 - Position of fairleads
 - Wind and current characteristics for the various drafts (vessels only)
 - Model tests results (if any)
 - Roll damping characteristics
 - Position of the unit with reference point
 - Heading of the unit (Spread moored unit)

- c) Anchoring/Mooring system
 - Identification of all mooring lines
 - Number and type of connections with the seabed and other structures
 - Mooring Geometry (number of legs, azimuth of the lines, anchors position)
 - Length of the mooring legs
 - Pre-tension (horizontal and/or axial and/or angle at fairlead)
 - Mooring legs composition
 - Information on corrosion
 - Hawser system description for buoys only (from connection of the buoy to the tanker)
- d) Site data
 - Site location
 - Site environmental conditions
 - Water Depth
- e) Survey and maintenance of mooring system
 - Survey reports
 - Maintenance reports & information
- f) Client assumptions for ERS Services
 - Design mooring force
 - Constraint on allowable horizontal excursion
 - Constraint on line tension (usage factor).

Note 1: The data should be given “as installed” or “as is” if modified since the installation.

4 Establishment of the Services

4.1 General

4.1.1 On pre-established mooring scenarios, the failure of one single line on site is considered.

4.1.2 The system is also checked against the subsequent failure of an additional line.

4.1.3 Results of such mooring analyses will give a basis in case of real incident and in particular will help to speed up the Service in case the incident corresponds to a pre-established scenario.

4.1.4 Such scenarios are very dependent upon the type of unit (buoy or F(P)SO), and the mooring system (spread mooring or single point mooring).

4.1.5 For buoys, calculations are performed with a static approach, tanker being modeled by the mooring force.

4.1.6 Pre-established mooring scenarios encompass a large number of configurations. The combinations of broken lines that will be studied are made to capture properly the maximum of response (horizontal excursions of the unit and tension in mooring lines).

4.1.7 Other configurations specific to each unit given by the Client in the contract may be investigated.

4.2 Configurations considered

4.2.1 Pre-established mooring scenarios are considered with the following configurations:

- Intact condition
- 1 broken line cases
- 2 broken line cases
- 2 drafts (full and ballast by default) except on vessels operating with a constant draft, this configuration is not applicable for buoys
- Different return periods of the environment defined in [3.3.2].

4.3 Methodology

4.3.1 F(P)SO – spread mooring

For a spread-moored F(P)SO, the methodology to assess the configurations in [4.2.1] follows the steps below:

- a) Calculations of environmental loads (intensity, direction) for each element (wave –swell and wind-sea-, current, wind) for all return periods
- b) Summation of all environmental loads for each direction for 100-year and 1-year return periods
- c) Determination of an envelope of vessel horizontal excursions: maximum excursion vs direction of the excursion for 100-year and 1-year return periods
- d) Determination of maximum tension in mooring lines for 100-year and 1-year return periods

4.3.2 F(P)SO – turret mooring

For a turret-moored F(P)SO, the methodology to assess the configurations in [4.2.1] follows the steps below:

- a) Calculations of environmental loads (intensity, direction) for 100-year and 1-year return periods
- b) Determination of an envelope of vessel horizontal excursions (maximum excursion vs direction of the excursion) for 100-year and 1-year return periods
- c) Determination of maximum mooring lines tension for 100-year and 1-year return periods.

4.3.3 Buoys

For buoys, the maximum tension in mooring lines and maximum buoy excursions will be assessed by applying a “design mooring force” (to be agreed for each unit) with a static approach.

The Client shall provide BV for each buoy with a constraint in excursions and/or a constraint in terms of line usage factor of mooring line strength. Based on this/these constraint(s), BV will provide maximum admissible mooring force to satisfy this/these constraint(s).

BV will calculate the required tug bollard pull to satisfy constraint in excursions and/or a constraint in terms of line usage factor of mooring line strength.

4.4 Side documentation

4.4.1 A report summarizing assumptions and results will be sent to the Client including:

- Mooring layout with line numbering conventions

- Stiffness of the mooring system for both drafts
 - in line / bundle direction
 - in between lines / bundles
- Results of analyses.

5 Emergency case

5.1 General

5.1.1 In an emergency case, the Client is to provide BV with the emergency form, identifying clearly the broken line(s).

5.1.2 The new configuration with the n broken lines is created to model the new mooring system after the incident

5.1.3 Calculations carried out by BV are based as far as possible on pre-established scenarios.

5.2 F(P)SO – spread mooring

5.2.1 Information provided by BV

BV will provide information on:

- a) Maximum horizontal excursion of the vessel and maximum mooring line tension over the remaining lines for the worst draft and for:
 - environment provided by the Client in the emergency form
 - 1-year return periods for the environment
 - 100-year return periods for the environment
- b) Minimum tug pull required to satisfy the Client horizontal excursion and mooring line tension criteria vessel for n broken line mooring system and for environment provided by the Client in the emergency form
- c) Maximum mooring line tension over the remaining lines and maximum horizontal excursion of the vessel for n broken line mooring system and with a tug pull specified by the Client if asked by the Client.

5.2.2 Methodology

Calculations will be based on the most severe vessel loading condition identified in pre-established scenarios.

Results of pre-established scenarios are used as far as possible concerning loads due to environments: for environment given by the Client, a similar environment will be determined from pre-established scenarios.

Depending on the number/nature of mooring lines broken during the incident, offsets and tensions may have to be recalculated.

In case of a large amount of broken lines resulting in a significant change of vessel behaviour (significant change of mean vessel heading), most results of pre-established scenarios may not be relevant and will be re-computed.

In all cases, methodology used will be as close as possible as the one used for pre-established scenarios

5.3 F(P)SO – turret mooring

5.3.1 Information provided by BV

BV will provide information about:

- a) Maximum horizontal excursion of the vessel and maximum mooring line tension over the remaining lines for the worst draft and for:
 - environment provided by the Client in the emergency form
 - 1-year return periods for the environment
 - 100-year return periods for the environment
- b) Minimum tug pull required to satisfy the Client horizontal excursion and mooring line tension criteria vessel for n broken line mooring system and for environment provided by the Client in the emergency form
- c) Maximum mooring line tension over the remaining lines and maximum horizontal excursion of the vessel for n broken line mooring system and with a tug pull specified by the Client if asked by the Client.

5.3.2 Methodology

Calculations will be based on the most severe vessel loading condition identified in pre-established scenarios.

Results of pre-established scenarios are used as far as possible concerning loads due to environments: for environment given by the Client, a similar environment will be determined from pre-established scenarios.

Depending on the number/nature of mooring lines broken during the incident, offsets and tensions may have to be recalculated.

In all cases, methodology used will be as close as possible as the one used for pre-established scenarios.

5.4 Buoys

5.4.1 Information provided by BV

For n broken line mooring systems, BV will provide information about:

- Maximum horizontal excursions and maximum mooring line tension over the remaining lines considering a “design mooring force” without tug
- Maximum mooring force satisfying the Client mooring line tension and /or offset criteria without tug
- Minimum tug pull required to satisfy constraint in tensions and/or excursions without considering mooring force
- At request of the Client and for an available tug bollard pull specified by the Client during the incident, BV will provide maximum horizontal excursions and maximum mooring line tension over the remaining lines.

5.4.2 Methodology

Analyses are based on a static approach with the same methodology as this described in 4 with n broken lines.

Achévé d'imprimer sur les presses d'Activ'Company
77 bd Exelmans - 75016 Paris (France)
Dépôt légal : December 2009