



**BUREAU  
VERITAS**

# **Methyl/ethyl alcohol Fuelled Ships**

**July 2021**

**Rule Note  
NR 670 DT R00 E**

**1. INDEPENDENCE OF THE SOCIETY AND APPLICABLE TERMS**

- 1.1 The Society shall remain at all times an independent contractor and neither the Society nor any of its officers, employees, servants, agents or subcontractors shall be or act as an employee, servant or agent of any other party hereto in the performance of the Services.
- 1.2 The operations of the Society in providing its Services are exclusively conducted by way of random inspections and do not, in any circumstances, involve monitoring or exhaustive verification.
- 1.3 The Society acts as a services provider. This cannot be construed as an obligation bearing on the Society to obtain a result or as a warranty. The Society is not and may not be considered as an underwriter, broker in Unit's sale or chartering, expert in Unit's valuation, consulting engineer, controller, naval architect, designer, manufacturer, shipbuilder, repair or conversion yard, charterer or shipowner; none of the above listed being relieved from any of their expressed or implied obligations as a result of the interventions of the Society.
- 1.4 Only the Society is qualified to apply and interpret its Rules.
- 1.5 The Client acknowledges the latest versions of the Conditions and of the applicable Rules applying to the Services' performance.
- 1.6 Unless an express written agreement is made between the Parties on the applicable Rules, the applicable Rules shall be the Rules applicable at the time of entering into the relevant contract for the performance of the Services.
- 1.7 The Services' performance is solely based on the Conditions. No other terms shall apply whether express or implied.

**2. DEFINITIONS**

- 2.1 "Certificate(s)" means classification or statutory certificates, attestations and reports following the Society's intervention.
- 2.2 "Certification" means the activity of certification in application of national and international regulations or standards ("Applicable Referential"), in particular by delegation from different governments that can result in the issuance of a Certificate.
- 2.3 "Classification" means the classification of a Unit that can result or not in the issuance of a classification Certificate with reference to the Rules. Classification (or Certification as defined in clause 2.2) is an appraisalment given by the Society to the Client, at a certain date, following surveys by its surveyors on the level of compliance of the Unit to the Society's Rules and/or to Applicable Referential for the Services provided. They cannot be construed as an implied or express warranty of safety, fitness for the purpose, seaworthiness of the Unit or of its value for sale, insurance or chartering.
- 2.4 "Client" means the Party and/or its representative requesting the Services.
- 2.5 "Conditions" means the terms and conditions set out in the present document.
- 2.6 "Industry Practice" means international maritime and/or offshore industry practices.
- 2.7 "Intellectual Property" means all patents, rights to inventions, utility models, copyright and related rights, trade marks, logos, service marks, trade dress, business and domain names, rights in trade dress or get-up, rights in goodwill or to sue for passing off, unfair competition rights, rights in designs, rights in computer software, database rights, topography rights, moral rights, rights in confidential information (including know-how and trade secrets), methods and protocols for Services, and any other intellectual property rights, in each case whether capable of registration, registered or unregistered and including all applications for and renewals, reversions or extensions of such rights, and all similar or equivalent rights or forms of protection in any part of the world.
- 2.8 "Parties" means the Society and Client together.
- 2.9 "Party" means the Society or the Client.
- 2.10 "Register" means the public electronic register of ships updated regularly by the Society.
- 2.11 "Rules" means the Society's classification rules (available online on [veristar.com](http://veristar.com)), guidance notes and other documents. The Society's Rules take into account at the date of their preparation the state of currently available and proven technical minimum requirements but are not a standard or a code of construction neither a guide for maintenance, a safety handbook or a guide of professional practices, all of which are assumed to be known in detail and carefully followed at all times by the Client.
- 2.12 "Services" means the services set out in clauses 2.2 and 2.3 but also other services related to Classification and Certification such as, but not limited to: ship and company safety management certification, ship and port security certification, maritime labour certification, training activities, all activities and duties incidental thereto such as documentation on any supporting means, software, instrumentation, measurements, tests and trials on board. The Services are carried out by the Society according to the Rules and/or the Applicable Referential and to the Bureau Veritas' Code of Ethics. The Society shall perform the Services according to the applicable national and international standards and Industry Practice and always on the assumption that the Client is aware of such standards and Industry Practice.
- 2.13 "Society" means the classification society 'Bureau Veritas Marine & Offshore SAS', a company organized and existing under the laws of France, registered in Nanterre under number 821 131 844, or any other legal entity of Bureau Veritas Group as may be specified in the relevant contract, and whose main activities are Classification and Certification of ships or offshore units.
- 2.14 "Unit" means any ship or vessel or offshore unit or structure of any type or part of it or system whether linked to shore, river bed or sea bed or not, whether operated or located at sea or in inland waters or partly on land, including submarines, hovercrafts, drilling rigs, offshore installations of any type and of any purpose, their related and ancillary equipment, subsea or not, such as well head and pipelines, mooring legs and mooring points or otherwise as decided by the Society.

**3. SCOPE AND PERFORMANCE**

- 3.1 Subject to the Services requested and always by reference to the Rules, and/or to the Applicable Referential, the Society shall:
- review the construction arrangements of the Unit as shown on the documents provided by the Client;
  - conduct the Unit surveys at the place of the Unit construction;
  - class the Unit and enter the Unit's class in the Society's Register;
  - survey the Unit periodically in service to note whether the requirements for the maintenance of class are met.
- The Client shall inform the Society without delay of any circumstances which may cause any changes on the conducted surveys or Services.
- 3.2 The Society will not:
- declare the acceptance or commissioning of a Unit, nor its construction in conformity with its design, such activities remaining under the exclusive responsibility of the Unit's owner or builder;
  - engage in any work relating to the design, construction, production or repair checks, neither in the operation of the Unit or the Unit's trade, neither in any advisory services, and cannot be held liable on those accounts.

**4. RESERVATION CLAUSE**

- 4.1 The Client shall always: (i) maintain the Unit in good condition after surveys; (ii) present the Unit for surveys; and (iii) inform the Society in due time of any circumstances that may affect the given appraisalment of the Unit or cause to modify the scope of the Services.
- 4.2 Certificates are only valid if issued by the Society.
- 4.3 The Society has entire control over the Certificates issued and may at any time withdraw a Certificate at its entire discretion including, but not limited to, in the following situations: where the Client fails to comply in due time with instructions of the Society or where the Client fails to pay in accordance with clause 6.2 hereunder.
- 4.4 The Society may at times and at its sole discretion give an opinion on a design or any technical element that would 'in principle' be acceptable to the Society. This opinion shall not presume on the final issuance of any Certificate nor on its content in the event of the actual issuance of a Certificate. This opinion shall only be an appraisalment made by the Society which shall not be held liable for it.

**5. ACCESS AND SAFETY**

- 5.1 The Client shall give to the Society all access and information necessary for the efficient performance of the requested Services. The Client shall be the sole responsible for the conditions of presentation of the Unit for tests, trials and surveys and the conditions under which tests and trials are carried out. Any information, drawing, etc. required for the performance of the Services must be made available in due time.
- 5.2 The Client shall notify the Society of any relevant safety issue and shall take all necessary safety-related measures to ensure a safe work environment for the Society or any of its officers, employees, servants, agents or subcontractors and shall comply with all applicable safety regulations.

**6. PAYMENT OF INVOICES**

- 6.1 The provision of the Services by the Society, whether complete or not, involves, for the part carried out, the payment of fees thirty (30) days upon issuance of the invoice.
- 6.2 Without prejudice to any other rights hereunder, in case of Client's payment default, the Society shall be entitled to charge, in addition to the amount not properly paid, interest equal to twelve (12) months LIBOR plus two (2)

per-cent as of due date calculated on the number of days such payment is delinquent. The Society shall also have the right to withhold Certificates and other documents and/or to suspend or revoke the validity of Certificates.

- 6.3 In case of dispute on the invoice amount, the undisputed portion of the invoice shall be paid and an explanation on the dispute shall accompany payment so that action can be taken to resolve the dispute.

**7. LIABILITY**

- 7.1 The Society bears no liability for consequential loss. For the purpose of this clause consequential loss shall include, without limitation:
- Indirect or consequential loss;
  - Any loss and/or deferral of production, loss of product, loss of use, loss of bargain, loss of revenue, loss of profit or anticipated profit, loss of business and business interruption, in each case whether direct or indirect.
- The Client shall defend, release, save, indemnify, defend and hold harmless the Society from the Client's own consequential loss regardless of cause.
- 7.2 Except in case of wilful misconduct of the Society, death or bodily injury caused by the Society's negligence and any other liability that could not be, by law, limited, the Society's maximum liability towards the Client is limited to one hundred and fifty per-cent (150%) of the price paid by the Client to the Society for the Services having caused the damage. This limit applies to any liability of whatsoever nature and howsoever arising, including fault by the Society, breach of contract, breach of warranty, tort, strict liability, breach of statute.
- 7.3 All claims shall be presented to the Society in writing within three (3) months of the completion of Services' performance or (if later) the date when the events which are relied on were first discovered by the Client. Any claim not so presented as defined above shall be deemed waived and absolutely time barred.

**8. INDEMNITY CLAUSE**

- 8.1 The Client shall defend, release, save, indemnify and hold harmless the Society from and against any and all claims, demands, lawsuits or actions for damages, including legal fees, for harm or loss to persons and/or property tangible, intangible or otherwise which may be brought against the Society, incidental to, arising out of or in connection with the performance of the Services (including for damages arising out of or in connection with opinions delivered according to clause 4.4 above) except for those claims caused solely and completely by the gross negligence of the Society, its officers, employees, servants, agents or subcontractors.

**9. TERMINATION**

- 9.1 The Parties shall have the right to terminate the Services (and the relevant contract) for convenience after giving the other Party thirty (30) days' written notice, and without prejudice to clause 6 above.
- 9.2 The Services shall be automatically and immediately terminated in the event the Client can no longer establish any form of interest in the Unit (e.g. sale, scrapping).
- 9.3 The Classification granted to the concerned Unit and the previously issued Certificates shall remain valid until the date of effect of the termination notice issued, or immediately in the event of termination under clause 9.2, subject to compliance with clause 4.1 and 6 above.
- 9.4 In the event where, in the reasonable opinion of the Society, the Client is in breach, or is suspected to be in breach of clause 16 of the Conditions, the Society shall have the right to terminate the Services (and the relevant contracts associated) with immediate effect.

**10. FORCE MAJEURE**

- 10.1 Neither Party shall be responsible or liable for any failure to fulfil any term or provision of the Conditions if and to the extent that fulfillment has been delayed or temporarily prevented by a force majeure occurrence without the fault or negligence of the Party affected and which, by the exercise of reasonable diligence, the said Party is unable to provide against.
- 10.2 For the purpose of this clause, force majeure shall mean any circumstance not being within a Party's reasonable control including, but not limited to: acts of God, natural disasters, epidemics or pandemics, wars, terrorist attacks, riots, sabotages, impositions of sanctions, embargoes, nuclear, chemical or biological contaminations, laws or action taken by a government or public authority, quotas or prohibition, expropriations, destructions of the worksite, explosions, fires, accidents, any labour or trade disputes, strikes or lockouts.

**11. CONFIDENTIALITY**

- 11.1 The documents and data provided to or prepared by the Society in performing the Services, and the information made available to the Society, will be treated as confidential except where the information:
- is properly and lawfully in the possession of the Society;
  - is already in possession of the public or has entered the public domain, other than through a breach of this obligation;
  - is acquired or received independently from a third party that has the right to disseminate such information;
  - is required to be disclosed under applicable law or by a governmental order, decree, regulation or rule or by a stock exchange authority (provided that the receiving Party shall make all reasonable efforts to give prompt written notice to the disclosing Party prior to such disclosure).
- 11.2 The Parties shall use the confidential information exclusively within the framework of their activity underlying these Conditions.
- 11.3 Confidential information shall only be provided to third parties with the prior written consent of the other Party. However, such prior consent shall not be required when the Society provides the confidential information to a subsidiary.
- 11.4 Without prejudice to sub-clause 11.1, the Society shall have the right to disclose the confidential information if required to do so under regulations of the International Association of Classification Societies (IACS) or any statutory obligations.

**12. INTELLECTUAL PROPERTY**

- 12.1 Each Party exclusively owns all rights to its Intellectual Property created before or after the commencement date of the Conditions and whether or not associated with any contract between the Parties.
- 12.2 The Intellectual Property developed by the Society for the performance of the Services including, but not limited to drawings, calculations, and reports shall remain the exclusive property of the Society.

**13. ASSIGNMENT**

- 13.1 The contract resulting from to these Conditions cannot be assigned or transferred by any means by a Party to any third party without the prior written consent of the other Party.
- 13.2 The Society shall however have the right to assign or transfer by any means the said contract to a subsidiary of the Bureau Veritas Group.

**14. SEVERABILITY**


- 14.1 Invalidation of one or more provisions does not affect the remaining provisions.
- 14.2 Definitions herein take precedence over other definitions which may appear in other documents issued by the Society.
- 14.3 In case of doubt as to the interpretation of the Conditions, the English text shall prevail.

**15. GOVERNING LAW AND DISPUTE RESOLUTION**

- 15.1 These Conditions shall be construed in accordance with and governed by the laws of England and Wales.
- 15.2 Any dispute shall be finally settled under the Rules of Arbitration of the Maritime Arbitration Chamber of Paris ("CAMP"), which rules are deemed to be incorporated by reference into this clause. The number of arbitrators shall be three (3). The place of arbitration shall be Paris (France). The Parties agree to keep the arbitration proceedings confidential.
- 15.3 Notwithstanding clause 15.2, disputes relating to the payment of the Society's invoices may be submitted by the Society to the *Tribunal de Commerce de Nanterre*, France, or to any other competent local Court, at the Society's entire discretion.

**16. PROFESSIONAL ETHICS**

- 16.1 Each Party shall conduct all activities in compliance with all laws, statutes, rules, economic and trade sanctions (including but not limited to US sanctions and EU sanctions) and regulations applicable to such Party including but not limited to: child labour, forced labour, collective bargaining, discrimination, abuse, working hours and minimum wages, anti-bribery, anti-corruption, copyright and trademark protection, personal data protection (<https://personaldataprotection.bureauveritas.com/prvacypolicy>).
- Each of the Parties warrants that neither it, nor its affiliates, has made or will make, with respect to the matters provided for hereunder, any offer, payment, gift or authorization of the payment of any money directly or indirectly, to or for the use or benefit of any official or employee of the government, political party, official, or candidate.
- 16.2 In addition, the Client shall act consistently with the Bureau Veritas' Code of Ethics and, when applicable, Business Partner Code of Conduct both available at <https://group.bureauveritas.com/group/corporate-social-responsibility/operational-excellence>.



## RULE NOTE NR 670

# NR 670 Methyl/ethyl alcohol Fuelled Ships

---

<b>SECTION 1</b>	<b>GENERAL</b>
<b>SECTION 2</b>	<b>RISK-BASED STUDIES</b>
<b>SECTION 3</b>	<b>SHIP DESIGN AND ARRANGEMENT</b>
<b>SECTION 4</b>	<b>FUEL CONTAINMENT SYSTEM</b>
<b>SECTION 5</b>	<b>MATERIAL AND GENERAL PIPE DESIGN</b>
<b>SECTION 6</b>	<b>BUNKERING EQUIPMENT</b>
<b>SECTION 7</b>	<b>FUEL SUPPLY TO CONSUMERS</b>
<b>SECTION 8</b>	<b>POWER GENERATION INCLUDING PROPULSION AND OTHER ENERGY CONVERTERS</b>
<b>SECTION 9</b>	<b>FIRE SAFETY</b>
<b>SECTION 10</b>	<b>EXPLOSION PREVENTION AND AREA CLASSIFICATION</b>
<b>SECTION 11</b>	<b>VENTILATION</b>
<b>SECTION 12</b>	<b>CONTROL AND MONITORING</b>
<b>SECTION 13</b>	<b>ADDITIONAL PROVISIONS FOR CHEMICAL TANKERS</b>

## **Section 1 General**

<b>1</b>	<b>General</b>	<b>5</b>
1.1	Application	
1.2	Classification notations	
1.3	Documentation to be submitted	
1.4	Definitions	

## **Section 2 Risk-Based Studies**

<b>1</b>	<b>Risk assessment</b>	<b>9</b>
1.1	Scope of the risk assessment	
1.2	Methodology	
<b>2</b>	<b>Limitation of explosion consequences</b>	<b>9</b>
2.1	Principle	
2.2	Additional requirements for explosion analysis	

## **Section 3 Ship Design and Arrangement**

<b>1</b>	<b>General</b>	<b>11</b>
1.1	Ship arrangement	
1.2	Design and arrangement of methyl/ethyl alcohol tanks	
1.3	Independent fuel tanks	
1.4	Portable tanks	
1.5	Machinery space	
1.6	Location and protection of fuel piping	
<b>2</b>	<b>Enclosed spaces design</b>	<b>12</b>
2.1	Bilge systems	
2.2	Drip trays	
2.3	Arrangement of entrances and other openings in enclosed spaces	
2.4	Airlocks	

## **Section 4 Fuel Containment System**

<b>1</b>	<b>Fuel containment system</b>	<b>14</b>
1.1	Requirements	
<b>2</b>	<b>Fuel tanks venting and gas freeing system</b>	<b>14</b>
2.1	Fuel tanks venting and gas freeing system	
<b>3</b>	<b>Inerting and atmospheric control within the fuel storage system</b>	<b>15</b>
3.1	General	
<b>4</b>	<b>Inert gas availability on board</b>	<b>15</b>
4.1	General	
<b>5</b>	<b>Airlocks</b>	<b>16</b>
5.1	General	

## **Section 5 Material and General Pipe Design**

<b>1</b>	<b>General</b>	<b>17</b>
	1.1	Classes of liquid and gas fuel piping systems
<b>2</b>	<b>General pipe design</b>	<b>17</b>
	2.1	General
	2.2	Piping fabrication and joining details
	2.3	Materials

## **Section 6 Bunkering Equipment**

<b>1</b>	<b>Bunkering station</b>	<b>20</b>
	1.1	General provisions
	1.2	Ships' bunker hoses
<b>2</b>	<b>Manifold</b>	<b>21</b>
	2.1	General
<b>3</b>	<b>Bunkering system</b>	<b>21</b>
	3.1	General

## **Section 7 Fuel Supply to Consumers**

<b>1</b>	<b>General</b>	<b>22</b>
	1.1	Fuel supply system
	1.2	Redundancy of fuel supply
	1.3	Safety functions of the fuel supply system
	1.4	Fuel preparation spaces and pumps

## **Section 8 Power Generation including Propulsion and other Energy Converters**

<b>1</b>	<b>General</b>	<b>23</b>
	1.1	General
	1.2	Internal combustion engines
	1.3	Provision for dual-fuel engines
	1.4	Provision for single fuel engines
	1.5	Methyl/ethyl alcohol-fuelled boilers

## **Section 9 Fire Safety**

<b>1</b>	<b>General</b>	<b>25</b>
	1.1	Application
	1.2	Provision for fire protection
<b>2</b>	<b>Fire detection</b>	<b>25</b>
	2.1	General

3	Provision for fire main	25
	3.1 General	
4	Fire fighting	25
	4.1 General	
5	Provision for fire extinguishing of engine-room and fuel preparation space	26
	5.1 General	

## **Section 10 Explosion Prevention and Area Classification**

1	General	27
	1.1 Means of reducing the probability of explosion	
	1.2 General provisions for hazardous areas	
	1.3 Area classification	
	1.4 Hazardous area zones	
	1.5 Electrical installations	

## **Section 11 Ventilation**

1	General	29
	1.1 Ventilation of hazardous areas	
	1.2 Fuel preparation spaces	
	1.3 Bunkering station	
	1.4 Ducts and double wall pipes	

## **Section 12 Control and Monitoring**

1	General	31
	1.1 General requirements	
2	Bunkering and fuel tank monitoring	31
	2.1 Level indicators for fuel tanks	
	2.2 Overflow control	
	2.3 Bunkering control	
	2.4 Engine monitoring	
	2.5 Gas detection	
	2.6 Safety functions of fuel supply systems	

## **Section 13 Additional Provisions for Chemical Tankers**

1	Chemical tankers using methyl/ethyl alcohol cargo as fuel	34
	1.1 General	
	1.2 Risk assessment	
	1.3 Ship arrangement	
	1.4 Fire protection and fire extinction	
	1.5 Cargo segregation	

# SECTION 1 GENERAL

## 1 General

### 1.1 Application

**1.1.1** This Rule Note provides requirements for the arrangement, installation, control and monitoring of machinery, equipment and systems using methyl/ethyl alcohol as fuel to minimize the risk to the ship, its crew and the environment, having regard to the nature of the fuels involved.

**1.1.2** This Rule Note incorporates requirements from IMO MSC.1/Circ.1621, which are applicable for Classification purposes.

**1.1.3** Ships using methyl/ethyl alcohol as fuel and falling within the scope of SOLAS Convention are to comply with the requirements of IMO IGF Code and Flag Administration rules as applicable.

**1.1.4** In accordance with the requirements of NR467, Pt A, Ch 1, Sec 2, ships complying with the requirements of this Rule Note will be eligible for assignment of a classification notation defined in [1.2].

Note 1: NR467 Rules for the Classification of Steel Ships.

Unless otherwise specified, the requirements of Sec 1 to Sec 12 are applicable to all ships.

In addition to the requirements of Sec 1 to Sec 12, ships assigned with the service notation **chemical tanker**, and designed to use methyl/ethyl alcohol cargo as fuel, are to comply with the requirements of Sec 13.

### 1.2 Classification notations

**1.2.1** Ships complying with the requirements of this Rule Note will be eligible for assignment of the additional service feature **methanolfuel** or **LFPfuel** for other alcohols as defined in NR467, Pt A, Ch 1, Sec 2, [4.13].

The additional service feature **methanolfuel** or **LFPfuel** is completed by:

- the notation **singlefuel** when the engine uses only methyl/ethyl alcohol as fuel
- the notation **dualfuel** when the engine uses methyl/ethyl alcohol fuel and oil fuel.

The additional service feature e.g. **methanolfuel dualfuel** or **methanolfuel singlefuel** may be completed by:

- the notation **-prop** when methyl/ethyl alcohol fuel is only used for propulsion systems
- the notation **-aux** when methyl/ethyl alcohol fuel is only used for auxiliary systems.

### 1.3 Documentation to be submitted

**1.3.1** With reference to [1.2], for ships to be assigned the additional service feature **methanolfuel** or **LFPfuel** for other alcohols, the documents listed in Tab 1 are to be submitted for approval or information.

### 1.4 Definitions

**1.4.1** For the purpose of this Rule Note, the terms used have the meanings defined in the following paragraphs. Terms not defined are to have the same meaning as in NR467 Rules for Steel Ships, NR566 Hull arrangement, stability and systems for ships less than 500 GT and NR529 Gas Fuelled Ships.

#### 1.4.2 Bunkering

Bunkering means the transfer of fuel from land-based or floating facilities into ships' permanent tanks or connection of portable tanks to the fuel supply system.

#### 1.4.3 Fuel

Fuel means methyl/ethyl alcohol fuels, containing allowable additives or impurities. Physical and chemical properties considered for the application of the present Rule Note are those of the products identified under CAS 67-56-1, UN 1230 or EC 00-659-6 for methyl alcohol and CAS 64-17-5, UN 1170, or EC 200-578-6 for ethyl alcohol.

#### 1.4.4 Fuel tank

Fuel tank is any integral, independent or portable tank used for storage of fuel. The spaces around the fuel tank are defined as follows:

- fuel storage hold space is the space enclosed by the ship's structure in which an independent fuel tank is located. If tank connections are located in the fuel storage hold space, a fuel storage hold space also is to be considered as tank connection space. Integral fuel tanks do not have a fuel storage hold space
- cofferdam is a structural space surrounding a fuel tank which provides an added layer of gas and liquid tightness protection against external fire and toxic and flammable vapours between the fuel tank and other areas of the ship
- tank connection space is a space surrounding all tank connections and tank valves that is required for tanks with such connections in enclosed spaces.

#### 1.4.5 Fuel preparation space

Fuel preparation space means any space containing equipment for fuel preparation purposes, such as fuel pumps, fuel valve train, heat exchangers and filters.

**1.4.6 Purging**

Purging means the introduction of inert gas into a tank which is already in an inert condition with the object of further reducing the oxygen content; and/or reducing the existing fuel or other flammable vapours content to a level below which combustion cannot be supported if air is subsequently introduced into the tank.

**1.4.7 Gas freeing**

Gas freeing is the process carried out to achieve a safe tank atmosphere. It includes two distinct operations:

- purging the hazardous tank atmosphere with an inert gas or other suitable medium (e.g. water) to dilute the hazardous vapour to a level where air can be safely introduced
- replacing the diluted inert atmosphere with air.

**1.4.8 Independent fuel tank**

Independent tanks are self-supporting, do not form part of the ship's hull and are not essential to the hull strength.

**1.4.9 Integral fuel tank**

Integral tank means a fuel-containment envelope tank which forms part of the ship's hull and which may be stressed in the same manner and by the same loads which stress the contiguous hull structure and which is normally essential to the structural strength of the ship's hull.

**1.4.10 Portable fuel tank**

Portable tank means an independent tank being able to be:

- easily connected and disconnected from ship systems and
- easily removed from ship and installed on board ship.

**1.4.11 Working pressure**

- Low pressure means a maximum working pressure lower than or equal to 1,0 MPa.
- High pressure means a maximum working pressure greater than 1,0 MPa but lower than or equal to 2,0 MPa.
- Very high pressure means a maximum working pressure greater than 2,0 MPa.

**1.4.12 Single failure**

Single failure is where loss of intended function occurs through one fault or action.

**1.4.13 Single fuel installation**

Single fuel engine means an engine capable of operating on a fuel as defined in [1.4.3].

**1.4.14 High fire risk spaces**

It includes as a minimum, but is not to be restricted to:

- a) cargo spaces except cargo tanks for liquids with flashpoint above 60°C and except cargo spaces exempted in accordance with SOLAS regulations II-2/10.7.1.2 or II-2/10.7.1.4
- b) vehicle, ro-ro and special category spaces
- c) service spaces (high risk): galleys, pantries containing cooking appliances, saunas, paint lockers and storerooms having areas of 4 m<sup>2</sup> or more, spaces for the storage of flammable liquids and workshops other than those forming part of the machinery space, as provided in SOLAS regulations II-2/9.2.2.4, II-2/9.2.3.3 and II-2/9.2.4, and
- d) accommodation spaces of greater fire risk: saunas, sale shops, barber shops, beauty parlors and public spaces containing furniture and furnishing of other than restricted fire risk and having deck area of 50 m<sup>2</sup> or more, as provided in SOLAS regulation II-2/9.2.2.3.

**Table 1 : Documentation to be submitted**

No.	I/A (1)	Documents
1	A	General arrangement of the ship showing the location of the bunkering stations, fuel tanks, TCS, fuel preparation rooms, vent masts, etc.
2	A	General arrangement of the machinery spaces containing the fuel utilization units (engines, turbines, boilers or gas combustion units)
3	I	Design statement that provides information about the intended service of the ship, including and the functionality of the main propulsion and auxiliary systems that use methyl/ethyl alcohol as fuel.
4	I	Operating manuals documents, to be kept on board, that indicate the installation particulars, including at least operating and maintenance instructions of fuel tanks, supply system and methyl/ethyl fuelled engines.
5	I	Bunkering operational procedures and maintenance instruction manuals.
6	I	Testing and trial procedure (including sea trials). The testing procedures are to include testing of safety shutdowns in accordance with the cause and effect diagram.
7	I	Arrangement of fuel tanks and/or fuel containment systems
8	I	Arrangement of fuel preparation spaces
9	I	Arrangement of fuel bunkering systems, including the bunkering connections
10	A	Arrangement of doors and openings within hazardous areas
11	A	Arrangement of entrances and air inlets leading of accommodation spaces, service spaces and control station spaces
12	A	Location and structure of air locks
13	A	Pipe, cable and duct penetrations in bulkheads and decks

No.	I/A (1)	Documents
14	A	Calculation of the hull temperature and associated distribution of quality and steel grades
15	A	Scantlings, material and arrangement of the fuel containment system, including the secondary barrier, if any
16	A	Sloshing calculation where relevant
17	A	Details of tank domes and deck sealings
18	A	Fuel containment system testing and inspection procedures
19	A	Vent mast detailed drawing
20	A	Description of coamings, drip trays and other protective measures
21	A	Hazardous area classification
22	I	Risk analysis report
23	A	Risk analysis recommendation follow-up
24	A	Details or instruction of fuel piping, including pressure relief valves and vent pipes for each fuel utilization unit
25	A	Technical documents for branches, return pipes, elbows, expansion joints, bellows and similar devices;
26	A	Drawing and instruction of flanges vent lines for pressure/ vacuum relief valves or similar piping and ducts for fuel pipes
27	A	Technical documents for the material, welding, post-weld heat treatment and non-destructive testing of fuel pipes;
28	I	Functional test guidelines for all piping, including valves, fittings and equipment relating to fuel (liquid or vapour) operation
29	A	Technical documents for electrical ground system of fuel pipes
30	I	Technical documents for the measures to remove the fuel from the fuel bunkering pipes before shutoff the bunkering connections
31	A	Fuel heating or cooling system
32	A	Diagram of the inert gas piping system
33	I	Fuel containment system gas freeing procedure, including emptying, inerting and aerating
34	A	Arrangement of bilge and drainage systems for fuel pump rooms and fuel tank connection spaces
35	I	Calculation for the discharge volume of pressure relief valves of pipes
36	A	Exhaust gas system, including arrangement of explosion relief
37	A	Interbarrier space drainage, inerting and pressurisation systems if fitted
38	A	Diagram of the fuel oil system including pilot fuel supply
39	A	Stress analysis of the high pressure piping systems
40	A	Arrangement and instruction of mechanical ventilation systems in hazardous areas and adjacent zones, including the capacity and arrangement of fans and their motors
41	A	Arrangement of the double piping or duct system
42	I	Fire Safety operational documentation including methyl/ethyl alcohol safety / emergency procedures
43	A	Arrangement and instruction (capacity calculation, etc.) of water spray systems, including pipes, valves, nozzles and fittings
44	A	Fire protection arrangement of fuel tanks and/or fuel storage hold spaces and their vent pipes, bunkering stations
45	A	Structural fire protection plan
46	A	External surface protection water spraying system
47	A	Bunkering station fire extinguishing system
48	A	Single line diagram of intrinsically safe circuits
49	A	List of certified explosion-proof equipment
50	A	Arrangement of electrical installation in hazardous areas, including lighting system
51	I	Safety certificates for electrical equipment located in hazardous spaces or zones, where applicable
52	A	Arrangement and instruction of fuel vapour detection and alarm systems, including probes, alarm arrangements and alarm set points
53	A	Arrangement and instruction of fuel tanks monitoring and control systems, including sensors and alarm set points
54	A	Arrangement and instruction of fuel pumps monitoring and control systems
55	A	Arrangement and instruction of methyl/ethyl alcohol fuelled engines monitoring and control systems
56	A	Arrangement and instruction of fire detection and alarm system
57	I	Type testing of the engine with electronic controls or a proposed test plan with the electronic controls operational
58	A	Arrangement and instruction of liquid leakage detection and alarm system

No.	I/A (1)	Documents
59	A	Emergency shutdown system
60	I	Dock and sea trials procedure relating to methyl/ethyl alcohol fuel, e.g. functional tests for all fuel piping and their valves, fittings and relevant equipment.
61	A	Tank hatches, pipes and any openings to tanks
62	A	Details of tanks coating
63	A	Detailed drawings of fuel tanks, materials, including internal structure, heat insulation (if any), piping, valves and connections
64	A	Detailed drawings of fuel tanks supporting
65	A	Pressure analysis of fuel tanks
66	I	Specification and type-approval reference of the fuel utilization units
67	A	Fabrication details of fuel tanks including building tolerances, NDT plan and welding procedures (WPS)
68	I	Procedure for maintenance of the fuel utilization units and other fuel-related equipment, including the steps to be taken prior to servicing the units
69	A	Diagram of the engine lubricating oil system
70	A	Diagram of the engine cooling system
71	A	Diagram of the engine crankcase venting systems
72	A	Drawings of the boilers, including burners
73	A	Fuel injection valves and drive and sealing system
74	A	Explosive protection and introduction of crankcase
75	A	Explosive protection and calculation of exhaust system
76	A	Schematic diagram of engine control system related to methyl/ethyl alcohol fuel (including monitoring, alarm and safety protection devices)
77	A	Schedule of testing at engine builders and commissioning prior to sea trials, including any testing required to verify the safeguards determined in the risk-assessment
78	A	HAZOP study if very high pressure fuel installations and report of the follow-up recommendations
79	A	FMECA analysis if very high pressure fuel equipment
80	A	FMEA analysis for the systems intended to maintain the fuel tank pressure and temperature
<b>(1)</b> I: for information A: for approval		

## SECTION 2

## RISK-BASED STUDIES

### 1 Risk assessment

#### 1.1 Scope of the risk assessment

**1.1.1** A risk assessment is to be conducted to ensure that risks arising from the use of methyl / ethyl alcohol fuels affecting persons on board, the environment, the structural strength or the integrity of the ship are addressed. Consideration is to be given to the hazards associated with physical layout, operation and maintenance, following any reasonably foreseeable failure.

**1.1.2** In addition to the requirements of this Section, Risk based studies for ships granted with the service notation **chemical tanker**, and designed to use methyl/ethyl alcohol cargo as fuel, are to comply with the provisions of Sec 13, [1.2].

#### 1.2 Methodology

**1.2.1** The risks are to be analysed using acceptable and recognized risk analysis techniques. Loss of function, component damage, fire, explosion, toxicity and electric shock are to, be considered, as a minimum. The analysis is to ensure that risks are eliminated wherever possible. Risks which cannot be eliminated are to be mitigated as necessary.

**1.2.2** The assessment is to be carried out in accordance with acceptable and recognized techniques described in the current version of, for example, ISO 31010 (Risk management - Risk assessment techniques), ISO 17776 (Petroleum and natural gas industries - Major accident hazard management during the design of new installations), ISO 16901 (Guidance on performing risk assessment in the design of onshore LNG installations including the ship/shore interface), NORSOK Z-013 (Risk and emergency preparedness assessment standard) or CPR 12E. (Methods for determining and processing probabilities).

**1.2.3** An HAZID study is to be carried out for each methyl/ethyl alcohol fuelled ship. It should cover at least the following spaces, zones and systems:

- tank connection space (TCS)
- enclosed and semi-enclosed fuel preparation rooms
- enclosed and semi-enclosed bunkering stations
- spaces containing very high pressure gas or liquid fuel piping
- ESD-protected machinery spaces
- spaces where fuel enclosure units are installed

- zones where vent lines and safety valve discharge lines are led, except where ventilation inlets to accommodation and machinery spaces are provided with gas detection arrangements (see Sec 12, [2.5.1]).

The risks identified by the HAZID study may be mitigated by operational procedures (e.g. stopping ship spaces ventilation during bunkering operations to prevent gas from entering those spaces through openings).

Where the requirements of this Rule Note for the arrangement of vents outlets cannot be satisfied due to size limits, gas dispersion analysis will be required to assess the risk associated with gas venting or pressure relief

**1.2.4** A FMECA analysis is to be carried out for the very high pressure equipment, including:

- pumps
- compressors
- diesel engines
- electrical generation and distribution systems as settled in IEC 60812.

**1.2.5** An HAZOP study is to be carried out for the very high pressure fuel installation. Type approved equipment need not be considered in the study.

**1.2.6** For any risk assessment carried out in the scope of the present Rule Note, a detailed follow-up report of actions and mitigation measures taken in response to any analysis findings is to be submitted to the Society.

### 2 Limitation of explosion consequences

#### 2.1 Principle

**2.1.1** An explosion in any space containing any potential sources of release and potential ignition sources is not to:

- a) cause damage to or disrupt the proper functioning of equipment/systems located in any space other than that in which the incident occurs
- b) damage the ship in such a way that flooding of water below the main deck or any progressive flooding occur;
- c) damage work areas or accommodation in such a way that persons who stay in such areas under normal operating conditions are injured
- d) disrupt the proper functioning of control stations and switchboard rooms necessary for power distribution;
- e) damage life-saving equipment or associated launching arrangements

- f) disrupt the proper functioning of fire-fighting equipment located outside the explosion-damaged space
- g) affect other areas of the vessel in such a way that chain reactions involving, inter alia, cargo, gas and bunker oil may arise
- h) prevent persons' access to life-saving appliances (LSA) or impede escape routes.

Note 1: Double wall fuel pipes are not considered as potential sources of release.

## **2.2 Additional requirements for explosion analysis**

**2.2.1** An explosion analysis is required for gas hazardous spaces, as a result of the risk assessment.

**2.2.2** Explosion analyses are to demonstrate that, for the worst case scenario, the maximum pressure built-up in case of explosion does not exceed the design pressure of the space, taking into account the venting arrangement and the explosion pressure relief devices, where provided.

**2.2.3** The worst case scenario is to assume a complete rupture of a fuel pipe and to take into account the following parameters:

- maximum expected time between the pipe rupture and the leakage detection
- time between the leakage detection and the gas supply shutoff
- ventilation flow rate.

**2.2.4** Where necessary, explosion pressure relief devices are to be provided.

## SECTION 3

## SHIP DESIGN AND ARRANGEMENT

### 1 General

#### 1.1 Ship arrangement

##### 1.1.1 Application

Unless otherwise specified, design and arrangement of ships granted with the additional service feature **methanol fuel** or **LFP fuel** for other alcohols are to comply with the requirements of this Section.

In addition to the requirements of this Section, ships granted with the service notation **chemical tanker**, and designed to use methyl/ethyl alcohol cargo as fuel, are to comply with the provisions of Sec 13, [1.3].

**1.1.2** Cofferdams surrounding fuel tanks are to be arranged either for purging or filling with water through a non-permanent connection. Emptying the cofferdams are to be done by a separate drainage system, e.g. bilge ejector.

**1.1.3** Where cofferdams surrounding integral fuel storage tanks are water filled, they are to be specially considered as ballast tanks in terms of corrosion addition and scantling as indicated in NR467, Pt B, Ch 4, Sec 2 and NR467, Pt B, Ch 7, Sec 1 to NR467, Pt B, Ch 7, Sec 3.

**1.1.4** Except for cargo area of tankers, all parts of methyl/ethyl alcohol system are to be located in enclosed spaces.

**1.1.5** Escape routes are to not pass through hazardous areas.

#### 1.2 Design and arrangement of methyl/ethyl alcohol tanks

**1.2.1** Tanks containing fuel are not to be located within accommodation spaces or machinery spaces of category A.

**1.2.2** Integral fuel tanks are to be surrounded by protective cofferdams, except on those surfaces bound by shell plating below the lowest possible waterline, other fuel tanks containing methyl/ethyl alcohol.

**1.2.3** All protective cofferdams are to be in accordance with Sec 12, [1.1.3].

**1.2.4** The fuel containment system is to be abaft of the collision bulkhead and forward of the aft peak bulkhead.

**1.2.5** Fuel tanks located on open decks are to be protected against mechanical damage.

**1.2.6** Fuel tanks on open decks are to be surrounded by coamings and spills are to be collected in a dedicated hold-tank complying with the requirements of [2.2.5].

**1.2.7** For single fuel installations, each fuel service tank is to have a capacity of at least 8 h at maximum continuous rating of the propulsion plant and normal operating load at sea of the generator plant.

**1.2.8** For dual fuel installations, engine is to be capable to switch to the other fuel in case of defiance.

**1.2.9** The tanks are to be designed according to strength requirements defined in NR467, Part B, Chapter 7.

**1.2.10** For single fuel installations, the fuel storage is to be divided between two or more tanks so that, in the event of any one tank becoming unavailable, the remaining tank(s) will provide sufficient fuel to enable the ship to operate within its service. These tanks are to be located in separate spaces. If those spaces are adjacent, the insulation between both spaces is to be at least A-60.

#### 1.3 Independent fuel tanks

**1.3.1** Independent tanks may be accepted on open decks or in a fuel storage hold space.

**1.3.2** Independent tanks are to be fitted with:

- mechanical protection of the tanks depending on location and cargo operations
- if located on an open deck, drip tray arrangements for leak containment and water spray systems for emergency cooling as indicated in Sec 9
- if located in a fuel storage hold space, the space is to meet the provisions of Sec 9 and Sec 11.

**1.3.3** Independent fuel tanks are to be secured to the ship's structure. The arrangement for supporting and fixing the tanks are to be designed for the maximum expected static, dynamic inclinations and accidental loads according to NR467, Pt C, Ch 1, Sec 1, [2.4] and NR467, Pt C, Ch 2, Sec 2, [1.6], as well as the accelerations according to NR467, Pt B, Ch 5, Sec 3 taking into account the ship's characteristics and the position of the tanks.

#### 1.4 Portable tanks

**1.4.1** Portable fuel tanks are to be located in dedicated areas fitted with:

- mechanical protection of the tanks depending on location and cargo operations
- if located on an open deck, drip tray arrangements for leak containment and water spray systems for emergency cooling as indicated in Sec 9
- if located in a fuel storage hold space, the space is to meet the provisions of Sec 9 and Sec 11.

**1.4.2** Portable fuel tanks are to be secured to the deck or hold space while connected to the ship systems. The arrangement for supporting and fixing the tanks are to be designed for the maximum expected static and dynamic inclinations according to NR467, Pt C, Ch 1, Sec 1, Tab 1 and NR467, Pt C, Ch 2, Sec 2, Tab 4, as well as the accelerations according to NR467, Pt B, Ch 5, Sec 3 taking into account the ship's characteristics and the position of the tanks.

**1.4.3** Consideration is to be given to the ship's strength and the effect of the portable fuel tanks on the ship's stability.

**1.4.4** Connections to the ship's fuel piping systems are to be made by means of approved flexible hoses suitable for methyl/ethyl alcohol or other suitable means designed to provide sufficient flexibility.

**1.4.5** Arrangements are to be provided to limit the quantity of fuel spilled in case of inadvertent disconnection or rupture of the non-permanent connections.

**1.4.6** The pressure relief system of portable tanks is to be connected to a fixed venting system.

**1.4.7** Control and monitoring systems for portable fuel tanks are to be integrated in the ship's control and monitoring system. A safety system for portable fuel tanks is to be integrated in the ship's safety system (e.g. shutdown systems for tank valves, leak / vapour detection systems).

**1.4.8** Safe access to tank connections for the purpose of inspection and maintenance is to be ensured.

**1.4.9** When connected to the ship's fuel piping system:

- each portable tank is to be capable of being isolated at any time
- isolation of one tank is not to impair the availability of the remaining portable tanks
- the tank is not to exceed its filling limits.

## **1.5 Machinery space**

**1.5.1** A single failure within the fuel system is not to lead to a release of fuel into the machinery space.

**1.5.2** All fuel piping within machinery space boundaries are to be enclosed in gas and liquid tight enclosures in accordance with Sec 7, [1.2].

## **1.6 Location and protection of fuel piping**

**1.6.1** Fuel pipes are not to be located less than 800 mm from the ship's side.

**1.6.2** Fuel piping are not to be led directly through accommodation spaces, service spaces, electrical equipment rooms or control stations.

**1.6.3** Fuel pipes led through ro-ro spaces, special category spaces and on open decks are to be protected against mechanical damage.

**1.6.4** Fuel piping that passes through enclosed spaces in the ship is to be enclosed in a pipe or duct that is gas and liquid tight towards the surrounding spaces with the fuel contained in the inner pipe. Such double walled piping is not required in cofferdams surrounding fuel tanks, fuel preparation spaces or spaces containing independent fuel tanks as the boundaries for these spaces will serve as a second barrier.

**1.6.5** The annular space between inner and outer pipe is to have mechanical ventilation of under pressure type with a capacity of minimum 30 air changes per hour and be ventilated to open air. Appropriate means for detecting leakage into the annular space are to be provided. The double wall enclosure is to be connected to a suitable draining tank allowing the collection and the detection of any possible leakage.

**1.6.6** Inerting of the annular space may be accepted as an alternative to ventilation. Appropriate means of detecting leakage into the annular space are to be provided. Suitable alarms are to be provided to indicate a loss of inert gas pressure between the pipes.

**1.6.7** The annular space is to be in accordance with Sec 11, [1.4] and Sec 12, [1.1.4].

**1.6.8** The outer pipe in the double walled fuel pipes is to be designed for a design pressure not less than the maximum working pressure of the fuel pipes.

**1.6.9** All fuel pipes are to be self-draining to suitable fuel or collecting tanks in normal condition of trim and list of the ship.

## **2 Enclosed spaces design**

### **2.1 Bilge systems**

**2.1.1** Bilge systems installed in areas where methyl/ethyl alcohol can be present should be segregated from the bilge system of spaces where methyl alcohol or ethyl alcohol cannot be present.

**2.1.2** One or more bilge holding tanks for collecting drainage and any possible leakage of methyl/ethyl alcohol from fuel pumps, valves or from double walled inner pipes located in enclosed spaces are to be provided. Means are to be provided for safely transferring contaminated liquids to onshore reception facilities.

**2.1.3** Bilge holding tanks must be sized to accumulate the maximum estimated leakage of fuel identified by the risk assessment.

**2.1.4** The bilge system serving the fuel preparation space is to be operable from outside the fuel preparation space.

### **2.2 Drip trays**

**2.2.1** Drip trays are to be fitted where leakage and spill may occur, in particular in way of single wall pipe connections.

**2.2.2** Each tray is to have a sufficient capacity to ensure that the maximum amount of spill according to the risk assessment can be handled.

**2.2.3** Each drip tray is to be provided with means to safely drain spills or transfer spills to a dedicated holding tank. Means for preventing backflow from the tank are to be provided.

**2.2.4** Drip trays for leakage of less than 10 litres may be provided with means for manual emptying.

**2.2.5** The leakage holding tank is to be equipped with a level indicator and alarm and is to be inerted at all times during normal operation.

### **2.3 Arrangement of entrances and other openings in enclosed spaces**

**2.3.1** Direct access is not to be permitted from a nonhazardous area to a hazardous area. Where such openings are necessary for operational reasons, an airlock which complies with the provisions of [2.4] is to be provided.

**2.3.2** Fuel preparation spaces are to have independent access direct from open deck. Where a separate access from open deck is not practicable, an airlock complying with [2.4] is to be provided.

**2.3.3** Fuel tanks and surrounding cofferdams are to have access from the open deck, where practicable, for gas freeing, cleaning, maintenance and inspection.

**2.3.4** Where direct access from the open deck is not practicable an entry space to fuel tanks or surrounding cofferdams is to be provided and is to comply with the following:

- a) be fitted with an independent mechanical extraction ventilation system, providing a minimum of six air changes per hour; a low oxygen alarm and a gas detection alarm are to be fitted
- b) have sufficient open area around the fuel tank hatch for efficient evacuation and rescue operation
- c) not be an accommodation space, service space, control station or machinery space of category A and
- d) a cargo space may be accepted as an entry space, depending upon the type of cargo, if the area is cleared of cargo and no cargo operation is undertaken during entry to the space.

**2.3.5** Where the surveyor requires to pass between the surface to be inspected, flat or curved, and structural elements such as deckbeams, stiffeners, frames, girders etc., the dis-

tance between that surface and the free edge of the structural elements is to be at least 380 mm. The distance between the surface to be inspected and the surface to which the above structural elements are fitted, e.g. deck, bulkhead or shell, is to be at least 450 mm in case of a curved tank surface or 600 mm in case of a flat tank surface.

**2.3.6** For safe access, horizontal hatches or openings to or within fuel tanks or surrounding cofferdams are to have a minimum clear opening of 600 mm x 600 mm that also facilitates the hoisting of an injured person from the bottom of the tank/cofferdam. For access through vertical openings providing main passage through the length and breadth within fuel tanks and cofferdams, the minimum clear opening are not to be less than 600 mm x 800 mm at a height of not more than 600 mm from bottom plating unless gratings or footholds are provided. Smaller openings may be accepted provided evacuation of an injured person from the bottom of the tank/cofferdam is demonstrated.

### **2.4 Airlocks**

**2.4.1** An airlock is a space enclosed by gastight bulkheads with two gastight doors spaced at least 1,5 m and not more than 2,5 m apart. Unless subject to the requirements of the International Convention on Load Lines, the door sill is not to be less than 300 mm in height. The doors are to be self-closing without any hold-back arrangements.

**2.4.2** Airlocks are to be mechanically ventilated at an over-pressure relative to the adjacent hazardous area or space.

**2.4.3** Airlocks are to have a simple geometrical form. They are to provide for free and easy passage, and are to have a deck area not less than 1,5 m<sup>2</sup>. Airlocks are not to be used for other purposes, for instance as storerooms.

**2.4.4** An audible and visual alarm system to give a warning on both sides of the airlock is to be provided to indicate if more than one door is moved from the closed position.

**2.4.5** For non-hazardous spaces with access from hazardous spaces below deck where the access is protected by an airlock, upon loss of under pressure in the hazardous space access to the space is to be restricted until the ventilation has been reinstated. Audible and visual alarms are to be given at a manned location to indicate both loss of pressure and opening of the airlock doors when pressure is lost.

**2.4.6** Airlocks are to be in accordance with Sec 4, [5].

## SECTION 4 FUEL CONTAINMENT SYSTEM

### 1 Fuel containment system

#### 1.1 Requirements

**1.1.1** The fuel tanks are to be designed such that a leakage from the fuel tank or its connections does not endanger the ship, persons on board or the environment. Potential dangers to be avoided include:

- flammable fuels spreading to locations with ignition sources
- toxicity potential and risk of oxygen deficiency or other negative impacts on crew health due to fuels and inert gases
- restriction of access to muster stations, escape routes or life-saving appliances (LSAs)
- reduction in availability of LSAs.

**1.1.2** The fuel containment system and the fuel supply system is to be designed such that safety actions after any leakage, irrespective of in liquid or vapour phase, do not lead to an unacceptable loss of power.

**1.1.3** If portable tanks are used for fuel storage, the design of the fuel containment system is to be equivalent to permanent installed tanks as described in this section.

### 2 Fuel tanks venting and gas freeing system

#### 2.1 Fuel tanks venting and gas freeing system

**2.1.1** The fuel tanks are to be fitted with a controlled tank venting system.

**2.1.2** Fuel tank venting system is to be independent of ventilation systems serving accommodation spaces, service spaces, control stations or other non-hazardous areas, and of air pipes from other tanks and piping systems.

**2.1.3** A fixed piping system is to be arranged to enable each fuel tank to be safely gas freed, and to be safely filled with fuel from a gas-free condition. In this regard, the following information is to be provided for verification:

- materials of construction of system
- time to gas free
- gas concentration inside the tank
- flow characteristics of fans to be used
- the pressure losses created by ducting, piping, fuel tank inlets and outlets
- the pressure achievable in the fan driving medium (e.g. water or compressed air)
- the densities of the fuel vapour / air mixture.

**2.1.4** The arrangement of internal tank structure and location of gas freeing inlets and outlets are to be such as to avoid the formation of gas pockets during the gas freeing operation.

**2.1.5** Pressure and vacuum relief valves are to be fitted to each fuel tank to limit the pressure or vacuum in the fuel tank. The tank venting system may consist of individual vents from each fuel tank or the vents from each individual fuel tank may be connected to a common header. Design and arrangement is to prevent flame propagation into the fuel containment system. If pressure relief valves (PRVs) of the high velocity type are fitted to the end of the vent pipes, they are to be certified for endurance burning in accordance with MSC/Circ.677. If PRVs are fitted in the vent line, the vent outlet is to be fitted with a flame arrestor certified for endurance burning in accordance with MSC/Circ.677.

**2.1.6** The fuel tank vent system is to be sized to permit bunkering at a design loading rate without over-pressurizing the fuel tank.

**2.1.7** The opening pressure of the PRVs is not to be lower than 0,007 MPa below atmospheric pressure.

**2.1.8** Shut-off valves are not to be arranged either upstream or downstream of the PRVs. Bypass valves may be provided. For temporary tank segregation purposes (maintenance) shut-off valves in common vent lines may be accepted if a secondary independent over/underpressure protection is provided to all tanks as per [2.1.10].

**2.1.9** The fuel tank-controlled venting system is to be designed with redundancy for the relief of full flow overpressure and/or vacuum. Pressure sensors fitted in each fuel tank, and connected to an alarm system, may be accepted in lieu of the secondary redundancy requirement for pressure relief.

**2.1.10** PRVs are to vent to a safe location on open deck and are to be of a type which allows the functioning of the valve to be easily checked.

**2.1.11** The fuel tank vent system is to be connected to the highest point of each tank and vent lines are to be selfdraining under all normal operating conditions.

**2.1.12** Fuel tank vent outlets are to be situated normally not less than 3 m above the deck or gangway if located within 4 m from such gangways. The vent outlets are also to be arranged at a distance of at least 10 m from the nearest air intake or opening to accommodation and service spaces and ignition sources. The vapour discharge is to be directed upwards in the form of unimpeded jets.

**2.1.13** Vapour outlets from fuel tanks are to be provided with devices tested and type approved to prevent the passage of flame into the tank. Due attention is to be paid in the design and position of the PRVs with respect to blocking and due to ice during adverse weather conditions. Provision for inspection and cleaning is to be arranged.

**2.1.14** The vent outlets are to be arranged in one of the following ways:

- outlets located at least 3 m above the deck level with a vertical efflux velocity of at least 30 m/s
- outlets located at least 3 m above the deck level with a vertical efflux velocity of at least 20 m/s which are protected by suitable devices to prevent the passage of flame
- underwater outlets.

### 3 Inerting and atmospheric control within the fuel storage system

#### 3.1 General

**3.1.1** The system is to be sized to be able keep the tanks inerted under during normal operation, gas freeing or inerting by utilizing an inerting medium.

**3.1.2** To prevent the return of flammable liquid and vapour to the inert gas system, the inert gas main supply line is to be fitted with two shutoff valves in series with a venting valve in between (double block and bleed valves). In addition, a closable non-return valve is to be installed between the double block and bleed arrangement and the fuel system. These valves are to be located inside hazardous spaces.

**3.1.3** Where the connections to the inert gas piping systems are non-permanent, two non-return valves may substitute the valves required in [3.1.2].

**3.1.4** Blanking arrangements are to be fitted in the inert gas supply line to individual tanks. The position of the blanking arrangements are to be immediately obvious to personnel entering the tank. Blanking is to be via removable spool piece.

**3.1.5** Fuel tank vent outlets should be situated normally not less than 3 m above the deck or gangway if located within 4 m from such gangways. The vent outlets are also to be arranged at a distance of at least 10 m from the nearest air intake or opening to accommodation and service spaces and ignition sources. The vapour discharge should be directed upwards in the form of unimpeded jets.

**3.1.6** Vapour outlets from fuel tanks should be provided with devices tested and type approved to prevent the passage of flame into the tank. Due attention should be paid in the design and position of the PRVs with respect to blocking and due to ice during adverse weather conditions. Provision for inspection and cleaning should be arranged.

**3.1.7** Gas freeing operations should be carried out such that vapour is initially discharged in one of the following ways:

- through outlets at least 3 m above the deck level with a vertical efflux velocity of at least 30 m/s maintained during the gas freeing operation
- through outlets at least 3 m above the deck level with a vertical efflux velocity of at least 20 m/s which are protected by suitable devices to prevent the passage of flame
- through outlets underwater.

**3.1.8** In designing a gas freeing system in conformity with [2.1.3] due consideration should be given to the following:

- materials of construction of system
- time to gas free
- flow characteristics of fans to be used
- the pressure losses created by ducting, piping, fuel tank inlets and outlets
- the pressure achievable in the fan driving medium (e.g. water or compressed air)
- the densities of the fuel vapour/air mixture.

### 4 Inert gas availability on board

#### 4.1 General

**4.1.1** Inert gas should be available permanently on board in order to achieve at least one trip from port to port considering maximum consumption of fuel expected and maximum length of trip expected and to keep tanks inerted during two weeks in harbour with minimum port consumption.

**4.1.2** A production plant and/or adequate storage capacities might be used to achieve availability target defined in [4.1.1].

**4.1.3** Fluid used for inerting is not to modify the characteristics of the fuel.

**4.1.4** The production plant, if fitted, is to be capable of producing inert gas with oxygen content at no time greater than 5% by volume. A continuous-reading oxygen content meter is to be fitted to the inert gas supply from the equipment and is to be fitted with an alarm set at a maximum of 5% oxygen content by volume. The system is to be designed to ensure that if the oxygen content exceeds 5% by volume, the inert gas is to be automatically vented to atmosphere.

**4.1.5** The system is to be able to maintain an atmosphere with an oxygen content not exceeding 8% by volume in any part of any fuel tank.

**4.1.6** An inert gas system is to have pressure controls and monitoring arrangements appropriate to the fuel containment system.

**4.1.7** Where a nitrogen generator or nitrogen storage facilities are installed in a separate compartment outside of the engine-room, the separate compartment is to be fitted with an independent mechanical extraction ventilation system, providing a minimum of six air changes per hour. If the oxygen content is equal or below 19% in the separate compartment, an alarm is to be given. A minimum of two oxygen sensors are to be provided in each space. Visual and audible alarms are to be placed at each entrance to the inert gas room.

**4.1.8** Inert gas piping system is not to pass through accommodation, service or control spaces.

**4.1.9** When inert gas pipes led through enclosed spaces piping system is to:

- have only a minimum of flange connections as needed for fitting of valves and be fully welded
- be as short as possible
- valves on the inert gas system are to be provided with nameplates indicating the tank, cofferdam or other space they serve.

**4.1.10** Notwithstanding the provisions of Article [4], inert gas utilized for gas freeing of tanks may be provided externally to the ship.

## 5 Airlocks

### 5.1 General

**5.1.1** Non-hazardous spaces with entry openings to a hazardous area are to be arranged with an airlock and be maintained at overpressure relative to the external hazardous area. The overpressure ventilation is to be arranged according to the following:

- a) during initial start-up or after loss of overpressure ventilation, before energizing any electrical installations not certified safe for the space in the absence of pressurization, it is to be required to:
  - proceed with purging (at least five air changes) or confirm by measurements that the space is non-hazardous; and
  - pressurize the space
- b) operation of the overpressure ventilation is to be monitored and in the event of failure of the overpressure ventilation:
  - an audible and visual alarm is to be given at a manned location; and
  - if overpressure cannot be immediately restored, automatic or programmed, disconnection of electrical installations according to a recognized standard is to be required.

Note 1: Refer to IEC 60092-502:1999 Electrical Installations in Ships – Tankers – Special Features, table 5.

**5.1.2** Non-hazardous spaces with entry openings to a hazardous enclosed space are to be arranged with an air-lock and the hazardous space is to be maintained at underpressure relative to the non-hazardous space. Operation of the extraction ventilation in the hazardous space is to be monitored and in the event of failure of the extraction ventilation:

- an audible and visual alarm is to be given at a manned location; and
- underpressure cannot be immediately restored, automatic or programmed, disconnection of electrical installations according to recognized standards in the nonhazardous space is to be required.

## SECTION 5

## MATERIAL AND GENERAL PIPE DESIGN

### 1 General

#### 1.1 Classes of liquid and gas fuel piping systems

**1.1.1** Piping systems are subdivided into three classes, denoted as class I, class II and class III, for the purpose of acceptance of materials, selection of joints, heat treatment, welding, pressure testing and the certification of fittings.

**1.1.2** Piping classes I, II and III are to be determined in accordance with the provisions of Tab 1.

**1.1.3** Liquid and gas fuel pressure vessels including surge tanks, heat exchangers and accumulators are to be considered as class 1 pressure vessels, in accordance with NR467, Pt C, Ch 1, Sec 3, [1.4].

### 2 General pipe design

#### 2.1 General

**2.1.1** All materials used are to be suitable for the fuel under the maximum working pressure and temperature.

**2.1.2** The design pressure for any section of the fuel piping system is the maximum gauge pressure to which the system may be subjected in service, taking into account the highest set pressure on any relief valve on the system.

**2.1.3** The wall thickness  $t$ , in mm, of pipes made of steel should not be less than:

$$t = \frac{(t_0 + b + c)}{\left(1 - \frac{a}{100}\right)}$$

where:

$t_0$  : theoretical thickness, in mm

$$t_0 = \frac{PD}{(2Ke + P)}$$

$P$  : system design pressure, in MPa, but not less than the design pressure given in [2.1.2]

$D$  : outside pipe diameter, in mm

$K$  : allowable stress, in N/mm<sup>2</sup> (see [2.1.4])

$e$  : efficiency factor equal to 1,0 for seamless pipes and for longitudinally or spirally welded pipes, delivered by approved manufacturers of welded pipes, which are considered equivalent to seamless pipes when non-destructive testing on welds is carried out in accordance with recognized standards. In other cases, an efficiency factor less than 1,0, in accordance with recognized standards, may be required depending upon the manufacturing process

$b$  : allowance for bending, in mm. The value for  $b$  should be chosen so that the calculated stress in the bend, due to internal pressure only, does not exceed the allowable stress. Where such justification is not given,  $b$  should not be less than:

$$b = Dt_0 / (2,5 r)$$

$r$  : mean radius of the bend, in mm

$c$  : corrosion allowance, in mm. If corrosion or erosion is expected, the wall thickness of piping should be increased over that required by the other design provisions

$a$  : negative manufacturing tolerance for thickness, in %.

**2.1.4** For pipes made of steel the allowable stress  $K$  to be considered in the formula for  $t_0$  in [2.1.3] is the lower of the following values:

$$R_m / A \text{ or } R_e / B$$

where:

$R_m$  : specified minimum tensile strength at ambient temperature (N/mm<sup>2</sup>)

$R_e$  : specified minimum yield stress at ambient temperature (N/mm<sup>2</sup>). If stress-strain curve does not show a defined yield stress, the 0,2% proof stress applies

The values of  $A$  and  $B$  should be at least:

$$A = 2,7 \text{ and } B = 1,8.$$

**2.1.5** Where necessary for mechanical strength to prevent damage, collapse, excessive sag or buckling of pipes due to superimposed loads, the wall thickness should be increased over that required by [2.1.3] or, if this is impracticable or would cause excessive local stresses, these loads should be reduced, protected against or eliminated by other design methods. Such superimposed loads may be due to supports, ship deflections, liquid pressure surge during transfer operations, the weight of suspended valves, reaction to loading arm connections or otherwise.

**2.1.6** For pipes made of materials other than steel, the allowable stress should be considered by the Society.

**2.1.7** High pressure fuel piping systems should have sufficient constructive and fatigue strength. This should be confirmed by carrying out stress analysis and taking into account:

- stresses due to the weight of the piping system
- acceleration loads when significant and
- internal pressure and loads induced by hog and sag of the ship.

**Table 1 : Classes of piping**

Piping system			Design conditions		Class of the gas piping		Class of the outer pipe (1)
			Design pressure	Design temperature	Single wall arrangement	Double wall arrangement (inner pipe)	
Gaseous fuel	Vent pipes (2)	From low pressure systems	p=5 bar (3)	all	class III	class III	class III
			p > 5 bar and p ≤ 10 bar (4)	all	class II	class III	class III
		From high pressure systems	p > 10 bar (4)	all	class I	class II	class III
Liquid fuel			all	all	class I	class I	class II

(1) The design pressure of the outer pipe or duct of fuel systems is to comply with Sec 3, [1.6.8]  
(2) Applies to open ended lines, namely:

- discharge lines from thermal relief valves
- discharge lines from tank pressure relief valves
- venting lines from "bleed" valves
- purging lines from engines and other gas consumers
- vent line from tank connection spaces

(3) The design pressure of vent pipes is not to be taken less than 5 bar.  
(4) The design pressure of the vent pipe is not to be less than the maximum expected pressure, which is to be justified

**2.1.8** Fuel pipes and all the other piping needed for safe and reliable operation and maintenance should be colour marked in accordance with a standard at least equivalent to those acceptable to the Society.

Note 1: Refer to EN ISO 14726:2008 Ships and marine technology – Identification colours for the content of piping systems.

**2.1.9** All fuel piping and independent fuel tanks are to be electrically bonded to the ship's hull. Electrical conductivity are to be maintained across all joints and fittings. Electrical resistance between piping and the hull is to be maximum 10<sup>6</sup> Ohm.

**2.1.10** Piping other than fuel supply piping and cabling may be arranged in the double wall piping or duct provided that it does not create a source of ignition or compromise the integrity of the double pipe or duct. The double wall piping or duct is to only contain piping or cabling necessary for operational purposes.

**2.1.11** Filling lines to fuel tanks are to be arranged to minimize the possibility for static electricity, e.g. by reducing the free fall into the fuel tank to a minimum.

**2.1.12** The arrangement and installation of fuel piping is to provide the necessary flexibility to maintain the integrity of the piping system in the actual service situations, taking potential for fatigue into account. Expansion bellows are not to be used.

## 2.2 Piping fabrication and joining details

**2.2.1** The inner piping, where a protective duct is required, is to be full penetration butt-welded, and fully radiographed. Flange connections in this piping are to only be permitted within the tank connection space and fuel preparation space or similar when:

- during the use of the fuel piping, all doors, ports and other openings on the corresponding superstructure or deckhouse side are to be kept closed and clearly indicated that this position is to be preserved during the operation; and
- the annular space in the double walled fuel piping is to be segregated at the engine-room bulkhead; this implies that there is to be no common ducting between the engine-room and other spaces.

**2.2.2** Piping for fuel is to be joined by welding except:

- for approved connections to shut-off valve and expansion joints, if fitted
- for other exceptional cases specifically approved by the Society.

**2.2.3** The following direct connections of pipe length without flanges may be considered:

- butt-welded joints with complete penetrations at the root
- slip-on welded joints with sleeves and related welding having dimensions in accordance with recognized standards is only to be used in pipes having an external diameter of 50 mm or less; the possibility for corrosion is to be considered
- screwed connections, in accordance with recognized standards, is only to be used for piping with an external diameter of 25 mm or less.

**2.2.4** Welding, post-weld heat treatment, radiographic testing, dye penetrating testing, pressure testing, leakage testing and non-destructive testing are to be performed in accordance with recognized standards. Butt welding is to be subject to 100% non-destructive testing, while sleeve welds are to be subject to at least 10% liquid penetrant testing (PT) or magnetic particle testing (MT).

**2.2.5** Where flanges are used, they are to be of the welded-neck or slip-on type. Socket welds are not to be used in nominal sizes above 50 mm.

**2.2.6** Expansion of piping is normally to be allowed for by the provision of expansion loops or bends in the fuel piping system. Use of expansion joints used in high pressure fuel systems are to be approved by the Society. Slip joints are not to be used.

**2.2.7** Piping connections are to be joined in accordance with [2.2.2], for other exceptional cases the Society may consider alternative arrangements.

## **2.3 Materials**

**2.3.1** Due consideration is to be taken with respect to the corrosive nature of fuel when selecting materials with special attention to the corrosive nature of methyl/ethyl alcohol when contaminated with water.

**2.3.2** In general, requirements for materials are to be in accordance with NR216 Rules on materials and welding.

**2.3.3** Materials for integrated tanks and independent tanks are to be selected in accordance with normal practice as given in NR467, Part B, Chapter 7.

**2.3.4** Materials, for tank coatings and tank access hatch sealing are to be resistant to:

- methyl/ethyl alcohol liquid
- methyl/ethyl alcohol where it may contain water
- methyl/ethyl alcohol vapour
- nitrogen gas used for inerting.

**2.3.5** Fluorinated materials such as Teflon may be used as equipment components in methyl alcohol service. Rubbers such as EPDM and neoprene are considered suitable for methyl alcohol service. Nitrile and butyl rubbers are not to be used in systems containing methyl alcohol fuel. The rubber hoses are to have an internal coil wire for strength and electrical continuity and are to be compatible with methyl alcohol service.

## SECTION 6

## BUNKERING EQUIPMENT

### 1 Bunkering station

#### 1.1 General provisions

**1.1.1** The bunkering station should be located on open deck so that sufficient natural ventilation is provided.

**1.1.2** Closed and semi-enclosed bunkering stations are to be protected from the effects of the sea.

**1.1.3** Closed and semi-enclosed bunkering stations are to be in accordance with Sec 11, [1.3].

**1.1.4** Closed or semi-enclosed bunkering stations are to be subject to special consideration within the risk assessment, which is to include but not be restricted to the following design features:

- segregation towards other areas on the ship
- hazardous area plans for the ship
- requirements for mechanical ventilation
- requirements for leakage detection (e.g. gas detection)
- safety actions related to leakage detection (e.g. gas detection)
- requirements for fire detection (e.g. flame detection)
- safety actions related to leakage detection (e.g. flame detection)
- access to bunkering station from non-hazardous areas through air locks; and
- monitoring of bunkering station by direct line of sight or by CCTV.

**1.1.5** Entrances, air inlets and openings to accommodation, service and machinery spaces and control stations are not to face the bunkering station.

**1.1.6** Closed or semi-enclosed bunkering stations are to be surrounded by gas and liquid-tight boundaries against enclosed spaces.

**1.1.7** Bunkering lines are not to be led directly through accommodation, control stations or service spaces. Bunkering lines passing through non-hazardous areas in enclosed spaces are to be in compliance with Sec 11, [1.3].

**1.1.8** Arrangements are to be made for safe management of fuel spills. Coamings and/or drip trays are to be provided below the bunkering connections together with a means of safely collecting and storing spills, such as a drain to a dedicated holding tank equipped with a level indicator and

alarm or other arrangements agreed by the classification society. Where coamings or drip trays are subject to rainwater, provisions are to be made to drain rainwater overboard.

**1.1.9** Showers and eye wash stations for emergency usage are to be located in close proximity to areas where the possibility for accidental contact with fuel exists. The emergency showers and eye wash stations are to be operable under all ambient conditions.

**1.1.10** Bunkering stations are not to be used for any other purpose than bunkering methyl/ethyl alcohol fuel.

#### 1.2 Ships' bunker hoses

**1.2.1** Bunker hoses carried on board are to be suitable for methyl/ethyl alcohol. Each type of bunker hose, complete with end-fittings, is to be prototype-tested at a normal ambient temperature, with 200 pressure cycles from zero to at least twice the specified maximum working pressure. After this cycle pressure test has been carried out, the prototype test is to demonstrate a bursting pressure of at least 5 times its specified maximum working pressure at the upper and lower extreme service temperature. Hoses used for prototype testing are not to be used for bunker service.

**1.2.2** Before being placed in service, each new length of bunker hose produced is to be hydrostatically tested at ambient temperature to a pressure not less than 1,5 times its specified maximum working pressure, but not more than two fifths of its bursting pressure. The hose is to be stencilled, or otherwise marked, with the date of testing, its specified maximum working pressure and, if used in services other than ambient temperature services, its maximum and minimum service temperature, as applicable. The specified maximum working pressure is not to be less than 1 MPa gauge.

**1.2.3** Means are to be provided for draining any fuel from the bunkering hoses upon completion of operation.

**1.2.4** Where fuel hoses are carried on board, arrangements are to be made for safe storage of the hoses. Hoses are to be stored on the open deck or in a storage room with an independent mechanical extraction ventilation system, providing a minimum of six air changes per hour.

**1.2.5** All bunker hoses are to be clearly labeled indicating their use only for methyl/ethyl alcohol. Hose ends are to be capped or protected by other suitable means to avoid contamination during storage.

## 2 Manifold

### 2.1 General

**2.1.1** The bunkering manifold is to be designed to withstand the external loads during bunkering. The connections at the bunkering station are to be of dry-disconnect type equipped with additional safety dry break-away coupling/self-sealing quick release. The couplings are to be of a standard type.

## 3 Bunkering system

### 3.1 General

**3.1.1** Means are to be provided for draining any fuel from the bunkering lines upon completion of operation.

**3.1.2** Bunkering lines are to be arranged for inerting and gas freeing.

**3.1.3** To ensure a rapid and safe shutdown of the bunker supply system without any release of liquid or vapour, a ship-shore link (SSL) or an equivalent means for automatic and manual ESD communication to the bunkering source operable from the bunker supply facility and the ship control station is to be fitted provided.

**3.1.4** In the bunkering line, as close to the connection point as possible, there is to be a manually operated stop valve and a remotely operated shutdown valve arranged in series. Alternatively, a combined manually operated and remote shutdown valve may be provided. It is to be possible to operate this remotely operated valve from the bunkering control station.

**3.1.5** Where bunkering lines are arranged with a crossover, suitable isolation arrangements are to be provided to ensure that fuel cannot be transferred inadvertently to the ship side not in use for bunkering.

## SECTION 7

## FUEL SUPPLY TO CONSUMERS

### 1 General

#### 1.1 Fuel supply system

**1.1.1** The fuel piping system should be separate from all other piping systems.

**1.1.2** The fuel supply system should be arranged such that the consequences of any release of fuel will be minimized, while providing safe access for operation and inspection. The causes and consequences of release of fuel should be subject to special consideration within the risk assessment in Sec 2, [1.2].

**1.1.3** The piping system for fuel transfer to the consumers should be designed in a way that a failure of one barrier cannot lead to a leak from the piping system into the surrounding area causing danger to the persons on board, the environment or the ship.

**1.1.4** Fuel lines should be installed and protected so as to minimize the risk of injury to persons on board in case of leakage.

#### 1.2 Redundancy of fuel supply

**1.2.1** Propulsion and power generation arrangements, are to be arranged so that a failure in fuel supply does not lead to an unacceptable loss of power

**1.2.2** For single fuel installations the fuel supply system is to be arranged with full redundancy and segregation all the way from the fuel tanks to the consumer, so that a leakage in one system does not lead to an unacceptable loss of power.

#### 1.3 Safety functions of the fuel supply system

**1.3.1** All fuel piping system is to be arranged for gas freeing and inerting.

**1.3.2** Fuel tank inlet and outlet valves are to be as close to the tank as possible. Valves required to be operated under normal operation, such as when fuel is supplied to consumers or during bunkering, are to be remotely operated if not easily accessible.

**1.3.3** The main fuel supply line to each consumer or set of consumers is to be equipped with an automatically operated master fuel valve. The master fuel valve(s) is to be situated in the part of the piping that is outside the machinery space con-

taining methyl/ethyl alcohol-fuelled consumer(s). The master fuel valve(s) is to automatically shut off the fuel supply in accordance with Sec 12, [2.6.1] and Sec 12, Tab 1.

**1.3.4** Means of manual emergency shutdown of fuel supply to the consumers or set of consumers are to be provided on the primary and secondary escape routes from the consumer compartment, at a location outside consumer space, outside the fuel preparation space and at the bridge. The activation device is to be arranged as a physical button, duly marked and protected against inadvertent operation and operable under emergency lighting.

**1.3.5** The fuel supply line to each consumer is to be provided with a remotely operated shut-off valve.

**1.3.6** All automatic and remotely operated valves are to clearly indicate whether they are in open or closed position where they are installed and where the valves are remotely operated.

**1.3.7** There is to be one manually operated shutdown valve in the fuel line to each consumer to ensure safe isolation during maintenance.

**1.3.8** Valves are to be of the fail-safe type.

**1.3.9** When pipes penetrate the fuel tank below the top of the tank a remotely operated shut-off valve are to be fitted to the fuel tank bulkhead.

#### 1.4 Fuel preparation spaces and pumps

**1.4.1** Any fuel preparation space is not to be located within a machinery space of category A, is to be gas and liquid tight to surrounding enclosed spaces and hold an independent ventilation system.

**1.4.2** Hydraulically powered pumps that are submerged in fuel tanks are to be arranged with double barriers preventing the hydraulic system serving the pumps from being directly exposed to methyl/ethyl alcohol. The double barrier is to be arranged for detection and drainage of eventual methyl/ethyl alcohol leakage.

**1.4.3** All pumps in the fuel system are to be protected against running dry (i.e. protected against operation in the absence of fuel or service fluid). All pumps which are capable of developing a pressure exceeding the design pressure of the system are to be provided with relief valves. Each relief valve is to be in closed circuit, i.e. arranged to discharge back to the piping upstream of the suction side of the pump and to effectively limit the pump discharge pressure to the design pressure of the system.

## SECTION 8

# POWER GENERATION INCLUDING PROPULSION AND OTHER ENERGY CONVERTERS

### 1 General

#### 1.1 General

**1.1.1** The exhaust system is to be designed to prevent any accumulation of unburnt fuel.

**1.1.2** The exhaust system is to be designed to withstand combustion of any fuel-air leak mixture by means of:

- a) explosion relief venting to prevent excessive pressure build-up. Where explosion relief venting is installed, the combustion products are to be vented to a safe location
- b) having sufficient strength to contain a worst-case explosion, in which case, evidences are to be submitted, or
- c) arrangements to prevent the exhaust system exceeding the auto-ignition temperature of the methyl/ethyl alcohol in addition to eliminating sources of ignition.

**1.1.3** Each fuel consumer is to have a separate exhaust system.

#### 1.2 Internal combustion engines

**1.2.1** One single failure in the fuel system is not to lead to an unacceptable loss of power.

**1.2.2** Methyl/ethyl alcohol engines are to be type approved on the basis of the following general and specific provisions for dual-fuel and single-fuel engines, in addition to those required in NR467, Pt C, Ch 1, Sec 2, for standard diesel engines.

**1.2.3** All engine components and engine-related systems are to be designed in such a way that fire and explosion risks are minimized.

**1.2.4** Engine components containing methyl/ethyl alcohol fuel are to be effectively sealed to prevent leakage of fuel into the machinery space.

**1.2.5** Fuel piping system is to be double walled. The efficiency of the inerting or ventilation arrangement of the double walled space is to be verified.

**1.2.6** A means are to be provided to monitor and detect poor combustion or misfiring. In the event that it is detected, continued operation may be allowed, provided that the fuel supply to the concerned cylinder is shut off and provided that the operation of the engine with one cylinder cut-off is acceptable with respect to torsional vibrations.

**1.2.7** The capability of engines driving generators to accept sudden load variations is to be verified.

**1.2.8** A risk assessment of the engine is to be carried out using an HAZID analysis or other acceptable methods and reflected in the safety concept of the engine. The risk assessment is to cover unless the following hazards:

- presence and possible accumulation of gaseous methyl/ethyl alcohol in the charge air system or in the crankcase
- condensation of methyl/ethyl alcohol vapours in the gas supply system
- leakage of high pressure liquid methyl/ethyl alcohol
- presence of unburnt methyl/ethyl alcohol vapours in the exhaust system
- failure of a methyl/ethyl alcohol admission valve or injection valve
- failure of the ignition system (spark plug or pilot injection)
- failure of the oil system (cooling and sealing)
- failure of the purging system.

The possible variations of the methyl/ethyl alcohol characteristics associated with its composition (density, flashpoint, heat value, flammability range) are to be considered.

#### 1.3 Provision for dual-fuel engines

**1.3.1** The lowest specified speed is to be verified in diesel mode and methyl/ethyl alcohol mode.

**1.3.2** In case of shut-off of the methyl/ethyl alcohol supply, the engines are to be capable of continuous operation by oil fuel only without interruption.

**1.3.3** An automatic system is to be fitted to change over from methyl/ethyl alcohol fuel operation to oil fuel operation with minimum fluctuation of the engine power. Acceptable reliability is to be demonstrated through testing. In the case of unstable operation on engines when methyl/ethyl alcohol firing, the engine is to automatically change to oil fuel mode. There is to also be the possibility for manual changeover.

**1.3.4** In case of an emergency stop or a normal stop, the methyl/ethyl alcohol fuel is to be automatically shut off not later than the pilot oil fuel. It is not to be possible to shut off the pilot oil fuel without first or simultaneously closing the fuel supply to each cylinder or to the complete engine.

## 1.4 Provision for single fuel engines

**1.4.1** In case of a normal stop or an emergency shutdown, the methyl/ethyl alcohol fuel supply is to be shut off not later than the ignition source. It is not to be possible to shut off the ignition source without first or simultaneously closing the fuel supply to each cylinder or to the complete engine.

## 1.5 Methyl/ethyl alcohol-fuelled boilers

**1.5.1** Boiler arrangements and burner systems are to be in accordance with the requirements of NR467, Pt C, Ch 1, Sec 3 and NR467, Pt C, Ch 1, Sec 10, or NR566 as applicable.

**1.5.2** The entire boiler casing is to be gastight and each boiler is to have a dedicated uptake.

**1.5.3** Unless it is incorporated in the burner, on the fuel pipe of each gas burner a shut-off valve and a flame arrestor is to be fitted.

**1.5.4** Combustion chambers and uptakes are to be designed to prevent any accumulation of gaseous fuel.

**1.5.5** Each boiler is to be provided with a dedicated forced draught system.

**1.5.6** In the event of a satisfactory ignition cannot be established or maintained, arrangements are to be provided to ensure that gas fuel flow to the burner is automatically cut off with a visual and audible alarm.

**1.5.7** Arrangements are to be provided for automatically and manually purging the fuel supply piping to the burners, after the extinguishing of these burners. Safety devices are to be fitted to ensure that purging can be carried out only when the burner fuel supply is shut off.

**1.5.8** On main/propulsion dual fuel boilers an automatic system is to be provided to change from methyl/ethyl alcohol fuel operation to oil fuel operation without interruption of boiler firing with the minimum impact to the flame.

**1.5.9** The automatic fuel changeover system required by **1.5.8** is to be monitored with alarms to ensure continuous availability.

**1.5.10** A low water condition is to automatically shut off the fuel supply to the burners with a visual and audible alarm as required in NR467, Pt C, Ch 1, Sec 3, [5.1.8] when boilers are operating on methyl/ethyl alcohol.

**1.5.11** Arrangements are to be provided to enable the boilers purging sequence to be manually activated.

## SECTION 9

## FIRE SAFETY

### 1 General

#### 1.1 Application

**1.1.1** Unless otherwise specified, design and arrangement of ships granted with the additional service feature **methanol fuel** or **LFP fuel** for other alcohols are to comply with the requirements of this Section.

In addition to the requirements of this Section, ships granted with the service notation **chemical tanker**, and designed to use methyl/ethyl alcohol cargo as fuel, are to comply with the provisions of Sec 13, [1.4].

#### 1.2 Provision for fire protection

**1.2.1** For the purposes of structural fire protection as addressed in NR467, Pt C, Ch 4, Sec 5, fuel preparation spaces are to be regarded as machinery space of category A. In addition, boundaries of the fuel preparation space towards other machinery spaces of category A, accommodation spaces, control stations or cargo areas are not to have fire integrity not less than A-60. Any boundary of accommodation spaces, service spaces, control stations, escape routes and machinery spaces, facing fuel tanks on open deck, shall be shielded by A-60 class divisions. The A-60 class divisions shall extend up to the underside of the deck of the navigation bridge.

**1.2.2** For fire integrity, the fuel tank boundaries are to be separated from the machinery spaces of category A and other rooms with high fire risks by a cofferdam of at least 600 mm, with insulation of not less than A-60 class.

**1.2.3** The bunkering station should be separated by A-60 class divisions from machinery spaces of category A, accommodation spaces, control stations and high fire risk spaces, except for spaces such as tanks, voids, auxiliary machinery spaces of little or no fire risk, sanitary and similar spaces where the insulation standard may be reduced to class A-0.

### 2 Fire detection

#### 2.1 General

**2.1.1** A fixed fire detection and fire alarm system complying with the IMO International Code for Fire Safety Systems (FSS Code).

**2.1.2** Suitable detectors are to be selected based on the fire characteristics of the fuel. Smoke detectors are to be used in combination with detectors which can more effectively detect methyl/ethyl alcohol fires.

**2.1.3** Means to ease detection and recognition of methyl/ethyl alcohol fires in machinery spaces are to be provided for fire patrols and for fire-fighting purposes, such as portable heat-detection devices.

**2.1.4** Fire detection in machinery space containing methyl/ethyl alcohol engines and fuel storage hold spaces is to give audible and visual alarms on the navigation bridge and in a continuously manned central control station or safety centre as well as locally.

**2.1.5** Fire detection system required in fuel preparation rooms, enclosed and semi enclosed bunkering stations and tank connection spaces, is to be in accordance with NR467, Pt C, Ch 4, Sec 15, [8].

### 3 Provision for fire main

#### 3.1 General

**3.1.1** When the fuel storage tank is located on the open deck, isolating valves are to be fitted in the fire main (on each side, aft and fore) in order to isolate sections damaged of the fire main in case of fire of the fuel storage tank. Isolation of a section of fire main is not to deprive the fire line ahead of the isolated section from the supply of water.

### 4 Fire fighting

#### 4.1 General

**4.1.1** Where fuel tanks are located on open deck, there is to be a fixed fire-fighting system of alcohol-resistant foam type, as set out in chapter 17 of the IBC Code and, where appropriate, chapter NR467 Pat D, Ch 7, Sec 6, [3]. The system is to be operable from a safe position.

**4.1.2** The alcohol-resistant foam type fire-fighting system is to cover the area below the fuel tank where a spill of fuel could be expected to spread.

**4.1.3** Foam from the fixed foam system is to be supplied by means of monitors and foam applicators. The capacity of any monitor shall be at least 10 l/min of foam solution per square metre of deck area protected by that monitor, such area being entirely forward of the monitor.

**4.1.4** The bunker station is to have a fixed fire-extinguishing system of alcohol resistant foam type and a portable dry chemical powder extinguisher or an equivalent extinguisher, located near the access of the bunkering station.

**4.1.5** Each powder or carbon dioxide extinguisher shall have a capacity of at least 5 kg and each foam extinguisher shall have a capacity of at least 9 l and be in accordance with NR467, Pt C, Ch 4, Sec 15, [3.2.1] or NR566 as applicable.

**4.1.6** Where fuel tanks are located on open deck, there is to be a fixed water spray system for diluting eventual spills, cooling and fire prevention. The system is to cover exposed parts of the fuel tank.

## **5 Provision for fire extinguishing of engine-room and fuel preparation space**

### **5.1 General**

**5.1.1** Machinery space and fuel preparation space where methyl/ethyl alcohol-fuelled engines or fuel pumps are arranged are to be protected by an approved fixed fire-extinguishing system in accordance with NR467, Pt C, Ch 4, Sec 6 and NR467, Pt C, Ch 4, Sec 15. In addition, the fire-extinguishing medium used is to be suitable for the extinguishing of methyl/ethyl alcohol fires.

**5.1.2** An approved alcohol-resistant foam system covering the tank top and bilge area under the floor plates is to be arranged for machinery space category A and fuel preparation space containing methyl/ethyl alcohol.

## SECTION 10

# EXPLOSION PREVENTION AND AREA CLASSIFICATION

### 1 General

#### 1.1 Means of reducing the probability of explosion

**1.1.1** The probability of explosions is to be reduced to a minimum by:

- reducing the number of sources of ignition
- reducing the probability of formation of ignitable mixtures, and
- using certified safe type electrical equipment suitable for the hazardous zone where the use of electrical equipment in hazardous areas is unavoidable.

#### 1.2 General provisions for hazardous areas

**1.2.1** Hazardous areas on open deck and other spaces not addressed in this section are to be analysed and classified based on a recognized standard ( Note 1). The electrical equipment fitted within hazardous areas are to be according to the same standard.

Note 1: Refer to IEC standard 60092-502:1999, part 4.4: Tankers carrying flammable liquefied gases, as applicable.

**1.2.2** All hazardous areas are to be inaccessible to passengers and unauthorized crew at all times.

**1.2.3** Essential equipment required for safety is not to be de-energized and is to be of a certified safe type. This may include lighting, fire detection, gas detection, public address and general alarms systems.

**1.2.4** Ventilation of hazardous areas are to be in accordance Sec 8, [1.1].

#### 1.3 Area classification

**1.3.1** Area classification is a method of analysing and classifying the areas where explosive gas atmospheres may occur. The object of the classification is to allow the selection of electrical apparatus able to be operated safely in these areas.

**1.3.2** In order to facilitate the selection of appropriate electrical apparatus and the design of suitable electrical installations, hazardous areas are divided into zones 0, 1 and 2, according to [1.4]. In cases where the prescriptive provisions in [1.4] are deemed to be inappropriate, area classification according to IEC 60079-10-1:2015 is to be applied with special consideration by The Society.

**1.3.3** Ventilation ducts are to have the same area classification as the ventilated space.

#### 1.4 Hazardous area zones

##### 1.4.1 Hazardous area zone 0

This zone includes, but is not limited to:

- the interiors of methyl/ethyl fuel tanks
- any pipework for pressure-relief or other venting systems for fuel tanks
- pipes and equipment containing methyl/ethyl fuel.

Instrumentation and electrical apparatus installed within these areas are to be of an intrinsically safe type (ATEX/Ex ia) suitable for zone 0.

##### 1.4.2 Hazardous area zone 1

This zone includes, but is not limited to:

- cofferdams and other protective spaces surrounding the fuel tanks
- fuel preparation spaces
- areas on open deck, or semi-enclosed spaces on deck, within 3 m of any methyl/ethyl fuel tank outlet, gas or vapour outlet, bunker manifold valve, other methyl/ethyl fuel valve, methyl/ethyl fuel pipe flange, methyl/ethyl fuel preparation space ventilation outlets
- areas on open deck or semi-enclosed spaces on deck in the vicinity of the fuel tank P/V outlets, within a vertical cylinder of unlimited height and 6 m radius centred upon the centre of the outlet and within a hemisphere of 6 m radius below the outlet
- areas on open deck or semi-enclosed spaces on deck, within 1.5 m of fuel preparation space entrances, fuel preparation space ventilation inlets and other openings into zone 1 spaces
- areas on the open deck within spillage coamings surrounding methyl/ethyl fuel bunker manifold valves and 3 m beyond these, up to a height of 2.4 m above the deck
- enclosed or semi-enclosed spaces in which pipes containing methyl/ethyl fuel are located, e.g. ducts around methyl/ethyl fuel pipes, semi-enclosed bunkering stations, and
- a space protected by an airlock is considered as non-hazardous area during normal operation, but will require equipment to operate following loss of differential pressure between the protected space and the hazardous area to be certified as suitable for zone 1
- air locks not protected by over pressure relative to the surrounding area but artificially ventilated, between hazardous area zone 1 and hazardous area zone 2.

Instrumentation and electrical apparatus installed within these areas are to be of a type suitable for zone 1.

### 1.4.3 Hazardous area zone 2

This zone includes, but is not limited to:

- areas 4 m beyond the cylinder and 4 m beyond the sphere defined in [1.4.2]
- areas within 1.5 m surrounding other open or semi-enclosed spaces of zone 1 defined in [1.4.2], and
- air locks protected by over pressure relative to the surrounding area, between hazardous area zone 1 and non-hazardous area
- air locks not protected by over pressure relative to the surrounding area but artificially ventilated, between hazardous area zone 2 and non-hazardous area.

Instrumentation and electrical apparatus installed within these areas are to be of a type suitable for zone 1.

## 1.5 Electrical installations

**1.5.1** Electrical installations are to comply with IEC 60092 series standards.

**1.5.2** Electrical equipment or wiring are not to be installed in hazardous areas unless essential for operational purposes or safety enhancement.

**1.5.3** Where electrical equipment is installed in hazardous areas as provided in [1.5.2], it is to be selected, installed and maintained in accordance with IEC. The types of electrical equipment admitted, depending on the zone where they are installed, are specified in Pt C, Ch 2, Sec 3, [10].

**1.5.4** The lighting system in hazardous areas is to be divided between at least two branch circuits. All switches and protective devices are to interrupt all poles or phases and are to be located in a non-hazardous area.

**1.5.5** The onboard installation of the electrical equipment units is to be such as to ensure the safe bonding to the hull of the units themselves.

**1.5.6** Electrical equipment which is not of the certified safe type for propulsion, power generation, maneuvering, anchoring and mooring equipment as well as the emergency fire pumps are not to be located in spaces to be protected by airlocks.

## SECTION 11

## VENTILATION

### 1 General

#### 1.1 Ventilation of hazardous areas

**1.1.1** Enclosed spaces classified hazardous areas are to be provided with mechanical ventilation capable to provide at least 8 changes per hour.

**1.1.2** Ventilation inlets and outlets for spaces to be equipped with mechanical ventilation should be located in such a way that, according to NR467, Pt B, Ch 8, Sec 10, [9.1.5], they are not required to have closing devices.

**1.1.3** Any ducting used for the ventilation of hazardous spaces is to be separate from that used for the ventilation of non-hazardous spaces. The ventilation is to be designed to work at all temperatures and environmental conditions the ship will be operating in.

**1.1.4** Electric motors for ventilation fans are not to be located in ventilation ducts for hazardous spaces unless the motors are certified for the same hazard zone as the space served.

**1.1.5** Design of ventilation fans serving spaces where vapours from fuels may be present is to fulfill the following:

- a) Ventilation fans are not to produce a source of vapour ignition in either the ventilated space or the ventilation system associated with the space; ventilation fans and fan ducts, in way of fans only, are to be of non-sparking construction defined as:
  - impellers or housings of non-metallic material, due regard being paid to the elimination of static electricity
  - impellers and housings of non-ferrous metals
  - impellers and housings of austenitic stainless steel
  - impellers of aluminium alloys or magnesium alloys and a ferrous (including austenitic stainless steel) housing on which a ring of suitable thickness of non-ferrous materials is fitted in way of the impeller, due regard being paid to static electricity and corrosion between ring and housing, or
  - any combination of ferrous (including austenitic stainless steel) impellers and housings with not less than 13 mm tip design clearance.
- b) In no case, the radial air gap between the impeller and the casing is to be less than 0,1 of the diameter of the impeller shaft in way of the bearing but not less than 2 mm; the gap need not be more than 13 mm, and
- c) Any combination of an aluminium or magnesium alloy fixed or rotating component and a ferrous fixed or rotating component, regardless of tip clearance, is considered a sparking hazard and are not to be used in these places.

**1.1.6** Ventilation systems required to avoid any vapour accumulation are to consist of independent fans, each of sufficient capacity, unless otherwise specified in these Interim Guidelines. The ventilation system is to be of a mechanical exhaust type, with extraction inlets located such as to avoid accumulation of vapour from leaked methyl/ethyl alcohol in the space.

**1.1.7** Air inlets for hazardous enclosed spaces are to be taken from areas that, in the absence of the considered inlet, would be non-hazardous. Air inlets for non-hazardous enclosed spaces are to be taken from non-hazardous areas at least 1,5 m away from the boundaries of any hazardous area. Where the inlet duct passes through a more hazardous space, the duct is to be gastight and have over-pressure relative to this space.

**1.1.8** Air outlets from non-hazardous spaces are to be located outside hazardous areas.

**1.1.9** Air outlets from hazardous enclosed spaces are to be located in an open area that, in the absence of the considered outlet, would be of the same or lesser hazard than the ventilated space.

**1.1.10** The required capacity of the ventilation plant is normally based on the total volume of the room. An increase in required ventilation capacity may be necessary for rooms having a complicated form.

**1.1.11** Double bottoms, cofferdams, duct keels, pipe tunnels, hold spaces and other spaces where methyl/ethyl fuel may accumulate are to be capable of being ventilated to ensure a safe environment when entry into the spaces is necessary.

**1.1.12** Any loss of required ventilation capacity in a hazardous area is to give an audible and visual alarm on the navigation bridge and in a continuously manned central control station or safety center as well as locally.

**1.1.13** An approved type fail-safe automatic closing fire damper is to be fitted in each ventilation trunk serving tank connection spaces, fuel preparation rooms or other hazardous enclosed spaces.

#### 1.2 Fuel preparation spaces

**1.2.1** Fuel preparation spaces are to be provided with an effective mechanical forced ventilation system of extraction type. During normal operation the ventilation is to be capable of provide at least 30 air changes per hour.

**1.2.2** The number and power of the ventilation fans are to be such that the capacity is not reduced by more than 50% if a fan with a separate circuit from the main switchboard or emergency switchboard or a group of fans with common circuit from the main switchboard or emergency switchboard is inoperable.

**1.2.3** Ventilation systems for fuel preparation spaces and other fuel handling spaces are to be interlocked with pumps or other fuel treatment equipment so as to prevent inadvertent operation if the ventilation is not operational.

### **1.3 Bunkering station**

**1.3.1** Bunkering stations that are not located on open deck are to be suitably ventilated to ensure that any vapour being released during bunkering operations will be removed outside. If the natural ventilation is not sufficient, the bunkering

stations are to be subject to special consideration with respect to provisions for mechanical ventilation. The Society may require special risk assessment.

### **1.4 Ducts and double wall pipes**

**1.4.1** Ducts and double wall pipes containing fuel piping fitted with a mechanical ventilation system of the extraction type are to be provided with a ventilation capacity of at least 30 air changes per hour.

**1.4.2** The ventilation system for double wall piping and ducts is to be independent of all other ventilation systems.

**1.4.3** The ventilation inlet for the double wall piping or duct is to always be located in a non-hazardous area, in open air, away from ignition sources. The inlet opening is to be fitted with a suitable wire mesh guard and protected from ingress of water.

## SECTION 12

## CONTROL AND MONITORING

### 1 General

#### 1.1 General requirements

**1.1.1** The control, monitoring and safety systems of the methyl/ethyl alcohol installations are to be arranged such that there is not an unacceptable loss of power in the event of a single failure.

**1.1.2** Suitable instrumentation devices are to be fitted to allow a local and a remote reading of essential parameters to ensure safe management of the whole fuel equipment including bunkering.

**1.1.3** Liquid leakage detection is to be installed in the protective cofferdams surrounding the fuel tanks, in all ducts around fuel pipes, in fuel preparation spaces, and in other enclosed spaces containing single walled fuel piping or other fuel equipment.

**1.1.4** The annular space in a double walled piping system is to be monitored for leakages and the monitoring system is to be connected to an alarm system. Any leakage detected is to lead to shutdown of the affected fuel supply line in accordance with Tab 1.

**1.1.5** At least one bilge well with a level indicator is to be provided for each enclosed space, where an independent storage tank without a protective cofferdam is located. A high-level bilge alarm is to be provided. The leakage detection system is to trigger an alarm and the safety functions in accordance with Tab 1.

**1.1.6** For tanks not permanently installed in the vessel, a monitoring system equivalent to that provided for permanent installed tanks is to be provided.

### 2 Bunkering and fuel tank monitoring

#### 2.1 Level indicators for fuel tanks

**2.1.1** Each fuel tank is to be fitted with closed level gauging devices, arranged to ensure a level reading is always obtainable.

**2.1.2** Unless any necessary maintenance can be carried out while the fuel tank is in service, two devices are to be installed.

#### 2.2 Overflow control

**2.2.1** Each fuel tank is to be fitted with a visual and audible high-level alarm. This is to be able to be function tested from the outside of the tank and can be common with the level gauging system (configured as an alarm on the gauging transmitter), but is to be independent of the high-high-level alarm.

**2.2.2** An additional sensor (high-high-level) operating independently of the high liquid level alarm is to automatically actuate a shut-off valve to avoid excessive liquid pressure in the bunkering line and prevent the tank from becoming liquid full.

**2.2.3** When water filling is the method for gas freeing the high and high-high-level alarm for the fuel tanks are to be visual and audible at the location at which gas freeing by water filling of the fuel tanks is controlled.

#### 2.3 Bunkering control

**2.3.1** Bunkering control is to be from a safe remote location. At this safe remote location:

- tank level is to be capable of being monitored
- the remote control valves required by Sec 6, [3.1.3] are to be capable of being operated from this location; closing of the bunkering shutdown valve is to be possible from the control location for bunkering and from another safe location, and
- overfill alarms and automatic shutdown are to also be indicated at this location.

**2.3.2** If the ventilation in the ducting enclosure or annular spaces of the double walled bunkering lines stops, an audible and visual alarm is to be activated at the bunkering control location.

**2.3.3** If fuel leakage is detected in ducting enclosure or the annular spaces of the double walled bunkering lines, an audible and visual alarm and emergency shutdown of the bunkering valve is to automatically be activated.

#### 2.4 Engine monitoring

**2.4.1** In addition to the instrumentation provided in accordance with NR467, Part C, Chapter 1 indicators are to be fitted on the navigation bridge, the engine control room and the manoeuvring platform for:

- operation of methyl/ethyl alcohol fuel engines, and
- operation and mode of operation of the engine in the case of dual fuel engines.

**Table 1 : Monitoring of methyl/ethyl alcohol supply system to engines**

Parameter	Alarm	Automatic shutdown of			Comments
		Tank valve (valve(s) referred to Sec 7, [1.4.2])	Master fuel valve (valve(s) referred to Sec 7, [1.4.3])	Bunkering valve	
High-level High-level fuel tank fuel tank	X			X	see [2.2.1]
High-high-level fuel tank	X			X	see [2.2.2] and [2.2.3]
Loss of ventilation in the annular space in the bunkering line	X			X	see [2.3.2]
Gas detection in the annular space in the bunkering line	X			X	see [2.3.3]
Loss of ventilation in ventilated areas	X			X	see Sec 11, [1.1.12]
Manual shutdown	X			X	see [2.3.1]
Liquid methyl/ethyl alcohol detection in the annular space of the double walled bunkering line	X			X	see [2.3.3]
Vapour detection in ducts around fuel pipes	X				see [2.5.1], item a)
Vapour detection in cofferdams surrounding fuel tanks. One detector giving 20% of LEL	X				see [2.5.5]
Vapour detection in airlocks	X				see [2.5.1], item g)
Vapour detection in cofferdams surrounding fuel tanks. Two detectors giving 40% of LEL	X	X	X		see [2.5.1], item f)
Vapour detection in ducts around double walled pipes, 20% of LEL	X				see [2.5.9]
Vapour detection in ducts around double walled pipes, 40% of LEL. Two gas detectors to give min. 40% of LEL before shutdown	X	X	X		see [2.5.9]
Oxygen detection in ducts around double walled pipes, giving 5% oxygen content by volume when inerted	X				see [2.5.6]
Oxygen detection in ducts around double walled pipes, giving 8% oxygen content by volume when inerted	X	X	X		see [2.5.6]
Oxygen detection in cofferdams surrounding fuel tanks, giving 5% oxygen content by volume when inerted	X				see [2.5.6]
Oxygen detection in cofferdams surrounding fuel tanks, giving 8% oxygen content by volume when inerted	X	X	X		see [2.5.6]
Loss of pressure in ducts around double walled pipes, when inerted	X				see [2.5.7]
Loss of pressure in cofferdams surrounding fuel tanks, when inerted	X				see [2.5.7]
Liquid leak detection in annular space of double walled pipes	X	X	X		see [1.1.4]
Liquid leak detection in engine room	X	X			see [1.1.3]
Liquid leak detection in fuel preparation space	X	X			see [1.1.3]
Liquid leakage detection in protective cofferdams surrounding fuel tanks	X				see [1.1.3]

## 2.5 Gas detection

**2.5.1** Permanently installed gas detectors are to be fitted in:

- a) all ventilated annular spaces of the double walled fuel pipes
- b) machinery spaces containing fuel equipment or consumers
- c) fuel preparation spaces
- d) other enclosed spaces containing fuel piping or other fuel equipment without ducting
- e) other enclosed or semi-enclosed spaces where fuel vapours may accumulate
- f) cofferdams and fuel storage hold spaces surrounding fuel tanks
- g) airlocks, and
- h) ventilation inlets to accommodation and machinery spaces if required based on the risk assessment required in Sec 2, [1.2.2].

**2.5.2** The number and placement of detectors in each space are to be considered taking into account the size, layout and ventilation of the space. Gas dispersal analysis or a physical smoke test is to be used to find the best arrangement.

**2.5.3** Fuel vapour detection equipment is to be designed, installed and tested in accordance with a recognized standard.

Note 1: Refer to IEC 60079-29-1:2016 - Explosive atmospheres - Gas detectors - Performance requirements of detectors for flammable gases.

**2.5.4** An audible and visible alarm is to be activated at a fuel vapour concentration of 20% of the lower explosion limit (LEL). The safety system is to be activated at 40% of LEL at two detectors. Special consideration is to be given to toxicity in the design process of the detection system.

**2.5.5** For ventilated ducts and annular spaces around fuel pipes in the machinery spaces containing methyl/ethyl alcohol-fuelled engines, the alarm limit is to be set to 20% of LEL. The safety system is to be activated at 40% of LEL at two detectors.

**2.5.6** When the double pipe or cofferdams surrounding fuel tanks are inerted, installation is to be in accordance with Sec 4.

**2.5.7** When the double pipe or cofferdams surrounding fuel tanks are inerted, an audible and visible alarm is to be activated at gas pressure less than 100 mm water gauge.

**2.5.8** Audible and visible alarms from the fuel vapour detection equipment are to be located on the navigation bridge, in the continuously manned central control station, safety centre and at the control location for bunkering as well as locally.

**2.5.9** Fuel vapour detection required by this section is to be continuous without delay.

## 2.6 Safety functions of fuel supply systems

**2.6.1** A fuel safety system is to be arranged to close down the fuel supply system automatically, upon failure in systems as described in Tab 1 and upon other fault conditions which may develop too fast for manual intervention.

**2.6.2** If the fuel supply is shut off due to activation of an automatic valve, the fuel supply is not to be opened until the reason for the disconnection is ascertained and the necessary precautions taken. A readily visible notice giving instruction to this effect is to be placed at the operating station for the shut-off valves in the fuel supply lines.

**2.6.3** If a fuel leak leading to a fuel supply shutdown occurs, the fuel supply is not to be operated until the leak has been found and dealt with. Instructions to this effect are to be placed in a prominent position in the machinery space.

**2.6.4** A caution placard or signboard is to be permanently fitted in the machinery space containing methyl/ethyl alcohol fuelled engines stating that heavy lifting, implying danger of damage to the fuel pipes, is not to be done when the engine(s) is running on methyl/ethyl.

**2.6.5** Pumps and fuel supply are to be arranged for manual remote emergency stop from the following locations as applicable:

- navigation bridge
- cargo control room
- onboard safety centre
- engine control room
- fire control station; and
- adjacent to the exit of fuel preparation spaces.

## SECTION 13

## ADDITIONAL PROVISIONS FOR CHEMICAL TANKERS

### 1 Chemical tankers using methyl/ethyl alcohol cargo as fuel

#### 1.1 General

**1.1.1** In addition to the requirements of Sec 2 to Sec 13, ships granted with the service notation **chemical tanker**, and designed to use methyl/ethyl alcohol cargo as fuel, are to comply with the requirement of [1.2] to [1.5].

#### 1.2 Risk assessment

**1.2.1** The following risks are to be considered in the risk assessment:

- the risk of fire or explosion in the cargo area that extends to the fuel supply system
- the risk of unforeseen transfer of contaminating or incompatible cargo to the fuel system
- when a cargo tank is dedicated as a fuel storage tank the risk of fire or explosion related to higher frequency of use of piping systems for transfer of fuel from service tank to engine room and transfer from a cargo tank to service tank.

#### 1.3 Ship arrangement

**1.3.1** A dedicated fuel service tank is to be provided. Except for the fuel transfer pipes from tanks for fuel storage, the piping system serving this tank is to be separated from cargo handling piping systems.

**1.3.2** Both fuel pump room and fuel service tank are to be located in the cargo area.

#### 1.4 Fire protection and fire extinction

**1.4.1** Fuel tanks are to be covered by the cargo deck fire extinguishing system and additional foam monitors or sprinklers are to be fitted where necessary.

**1.4.2** Boundaries of fuel pump room and fuel service tank are to be protected by a water spray system for fire prevention and cooling. The system with a uniformly distributed water application rate of at least 10 litre/m<sup>2</sup>/min for the largest projected horizontal surfaces and 4 litre/m<sup>2</sup>/min for vertical surfaces.

**1.4.3** The capacity of the water spray pump is to be sufficient to deliver the required amount of water to the hydraulically most demanding area as specified in [1.4.2] in the areas protected.

**1.4.4** If the water spray system is not part of the fire main system, a connection to the ships fire main through a stop valve is to be provided.

#### 1.5 Cargo segregation

**1.5.1** When a cargo tank located within the cargo area is used as fuel storage tank, this cargo tank is to be dedicated as fuel tank when ship is operating on methyl/ethyl alcohol as fuel.

**1.5.2** Fuel cargo tank cannot adjacent to cargo tanks carrying cargoes that are not compatible with methyl/ethyl alcohol.

**1.5.3** All cargo pipes dedicated to fuel use are to be separated from other cargo piping serving other tanks.

**1.5.4** The venting system for a dedicated fuel cargo tank is to be separated from other cargo venting systems.

**1.5.5** When the ship is arranged to operate only with methyl/ethyl alcohol as fuel, if the fuel service tank is located within the cargo area, the ship is to be provided with an alternative power supply system to ensure all essential services onboard.



**BUREAU  
VERITAS**

Shaping a World of Trust

Marine & Offshore  
Le Triangle de l'Arche - 8 Cours du Triangle - CS 50101  
92937 Paris La Defense Cedex - France  
Tel: + 33 (0)1 55 24 70 00  
<https://marine-offshore.bureauveritas.com/bv-rules>  
© 2021 Bureau Veritas – All rights reserved